


Data sheet

3794.1 ZAP SR 3A/15 GN



End plate, Width: 1.6 mm, Colour: Green

Business data

Article number	3794.1
Article name	ZAP SR 3A/15 GN
GTIN (EAN)	4044211061227
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.84 g
Weight per piece (including packaging)	1.89 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	3794.2
Product description	End plate

Data sheet

3794.1 ZAP SR 3A/15 GN



Technical data

Dimensions

Length	52.5 mm
Width	1.6 mm
Height	28.7 mm

Materials

Material	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Designed as end plate	✓
Snap-on available	✓

Environmental Product Compliance

REACH Conform	Yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	Yes

Media

Accessories

##INVERSE##CONTA-CONNECT




Protective earth terminal, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3601.2</u>	ZSLN 2,5/3A/15 GNYE	4044211152048	100 ST




Ex protective-earth terminal ATEX-certified Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1710.2</u>	ZSLN 2,5/3A/15 Ex GNYE	4044211059651	100 ST



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3599.2</u>	ZSRK 2,5/3A/15 BG	4044211152024	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1701.2</u>	ZSRK 2,5/3A/15 Ex BG	4044211059590	100