## **SIEMENS**

## **Data sheet**



Pushbutton, 22 mm, round, plastic, black, Front ring, raised, castellated momentary contact type, with laser labeling, lower case  $\,$ 

product brand name	SIRIUS ACT
product designation	Pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Plastic, black, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Flat button
principle of operation of the actuating element	momentary contact type
product extension optional	
• light source	No
contact module	Yes
color of the actuating element	black
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	29.5 mm
marking of the actuating element	Customized labeling, text in lower case letters
Front ring	
product component front ring	Yes
design of the front ring	high with crenellations
material of the front ring	plastic
color of the front ring	black
General technical data	
protection class IP	IP66, IP67, IP69(IP69K)
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance	
shock resistance • acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms
	Sinusoidal half-wave 50g / 11 ms Category 1, Class B
• acc. to IEC 60068-2-27	
<ul><li>acc. to IEC 60068-2-27</li><li>for railway applications acc. to DIN EN 61373</li></ul>	
<ul> <li>acc. to IEC 60068-2-27</li> <li>for railway applications acc. to DIN EN 61373</li> <li>vibration resistance</li> </ul>	Category 1, Class B
<ul> <li>acc. to IEC 60068-2-27</li> <li>for railway applications acc. to DIN EN 61373</li> <li>vibration resistance</li> <li>acc. to IEC 60068-2-6</li> </ul>	Category 1, Class B  10 500 Hz: 5g
<ul> <li>acc. to IEC 60068-2-27</li> <li>for railway applications acc. to DIN EN 61373</li> <li>vibration resistance</li> <li>acc. to IEC 60068-2-6</li> <li>for railway applications acc. to DIN EN 61373</li> </ul>	Category 1, Class B  10 500 Hz: 5g Category 1, Class B
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373  vibration resistance acc. to IEC 60068-2-6 for railway applications acc. to DIN EN 61373  operating frequency maximum	Category 1, Class B  10 500 Hz: 5g Category 1, Class B 3 600 1/h
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373  vibration resistance acc. to IEC 60068-2-6 for railway applications acc. to DIN EN 61373  operating frequency maximum mechanical service life (switching cycles) typical	Category 1, Class B  10 500 Hz: 5g Category 1, Class B 3 600 1/h 10 000 000

ambient temperature during storage	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	18.1 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-0DB10-0AA0-Z Y12

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1000-0DB10-0AA0-Z\ Y12}$ 

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-0DB10-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1000-0DB10-0AA0-Z Y12&lang=en

last modified: 12/21/2020 🖸