

Industrial Power Strip, 3-Outlet, 6 ft. (1.8 m) Cord, NEMA 5-15P Plug, Switch Guard

MODEL NUMBER: 3SP











Highlights

- 3 outlets
- 6-ft. (1.83 m) cord
- 8.6 in. overall length
- Lighted master power switch

Package Includes

- 3SP Power Strip
- · Warranty information
- Instruction manual

Description

The 3SP power strip offers a convenient method of power distribution in workbench, wall-mount or floor-mount applications. Includes three NEMA 5-15R output receptacles with 1.75-inch center-to-center spacing, six-foot (1.8-meter) AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cable clutter and permits connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 3SP ideal for distributing alternate waveform UPS or generator power. Features a rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive blue/gray color scheme.

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs for installation on a wide variety of applications
- UL1363 (USA), cUL (Canada)
- 15-amp power handling capacity with circuit breaker
- 6-ft. (1.83 m) AC line cord

Specifications

| OVERVIEW | | |
|------------------------------------|--------------|--|
| UPC Code | 037332103321 | |
| | | |
| INPUT | | |
| Nominal Input Voltage(s) Supported | 120V AC | |



| Recommended Electrical Service | 15A 120V | |
|---|---|--|
| Voltage Compatibility (VAC) | 120 120 120 120 120 120 120 120 120 120 | |
| | | |
| Input Plug Type | NEMA 5-15P | |
| Input Cord Length (ft.) | 6 | |
| Right-Angle Plug | No | |
| Input Cord Length (m) | 1.83 | |
| Integrated Cord Clip | No | |
| OUTPUT | | |
| Frequency Compatibility | 50 / 60 Hz | |
| Output Receptacles | (3) 5-15R | |
| Circuit Breaker (amps) | 15 | |
| Transformer Accommodation | (1) Yes | |
| Outlet Orientation | Single row of 3 | |
| Right-Angle Outlets | No | |
| Outlet Spacing | 1.75 in. | |
| USER INTERFACE, ALERTS & CONTROLS | | |
| Switches | Lighted 2 position switch controls power to all outlets | |
| | | |
| Locking Switch Cover | Transparent locking switch cover prevents accidental shutoff | |
| PHYSICAL | | |
| Color | Gray | |
| Material of Construction | Metal | |
| Power Cord Color | Black | |
| Housing Color | Blue; Gray | |
| Mounting Holes or Slots | Yes | |
| Slot or Hole Mount Measurement (Center to Center) | Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm | |
| Receptacle Color | Black | |
| Shipping Dimensions (hwd / in.) | 2.00 x 5.20 x 9.80 | |
| Shipping Dimensions (hwd / cm) | 5.08 x 13.21 x 24.89 | |
| Shipping Weight (lbs.) | 1.60 | |
| Shipping Weight (kg) | 0.73 | |
| Unit Dimensions (hwd / in.) | 1.500 x 8.750 x 2.500 | |
| | | |
| Unit Dimensions (hwd / cm) | 18.7 x 6.35 x 3.8 | |



| Mounting Details | Includes flanges | |
|-------------------------------------|--------------------------------|--|
| FEATURES & SPECIFICATIONS | | |
| Antimicrobial | No | |
| Built-In Circuit Breaker | Yes | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | cUL Listed; UL 1363; UL Listed | |
| Product Compliance | RoHS | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.