



CORE DIMENSIONS					40T0232-200	
UNCOATED CORE						
	MM	INCHES		MM	INCHES	
OD	5.84	(.230)	±	.15	(.006)	
ID	3.05	(.120)	±	.15	(.006)	
TH	1.65	(.065)	±	.15	(.006)	
SINGLE PARAYLENE					40T0232-20P	
OD	5.87	(.231)	±	.15	(.006)	
ID	3.02	(.119)	±	.15	(.006)	
TH	1.68	(.066)	±	.15	(.006)	

WEIGHT / K 0.1569 KGS .3459 LBS
 INITIAL PERMEABILITY 10000

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L1-1T	-30.0%	1.50	2.147	2.79	30.0%	100	0.99	10	1

COATING SPECIFICATIONS			
TYPE	Ref. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Paraylene	(0.0127 / 0.5)	1000	.30

NOTES:
 1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	New release	2020/4/12	WS

Date: 2020/4/12	Tooling T0232	Rev: A
Drawn By: WS	Title # 40T0232-20P	

Laird This document contains information which is proprietary to laird. No production or publication of this document in whole or in part shall be made without written authorization from Laird.