

# ETHERLINE® 2 pair: CAT.5/CAT.5e; flexible

## Industrial Ethernet cable for flexible applications



Flexible ETHERLINE® CAT.5/5e cables are constructed with a high-quality foil and copper braid shield for reliable data transfer in areas where EMI is pervasive. The different jacket materials provide excellent protection against oil, flame, or sunlight. A Low Smoke Zero Halogen (LSZH) jacketed cable is available for applications where human safety and damage to electronic components are a concern.

### Recommended applications

Flexible applications; wiring of industrial network devices, sensors, actuators, and cordsets

### Approvals



### Construction

**Conductors:** stranded bare copper • 2170886: stranded tinned copper

**Pairs:** 2 twisted pairs or star quad




**Insulation:** polyethylene • 2170901: polyolefin

**Shielding:** foil and copper braid

**Jacket:** PVC; green or black • polyurethane or halogen-free; teal

### Application advantage

- Excellent EMI protection
- Oil-, flame- & UV-resistant jacket
- Conforms to PROFINET® standard
- Suitable for EtherCAT® & EtherNet/IP applications
- Fast connect style allows for quick installation
- Suitable for PoE per IEEE 802.3at (see table below)

Cable attributes <span style="float: right;">page 648</span>	Complete the installation	ÖLFLEX® CONNECT solution
See attribute list by part number on page 232	 Fast connect stripping tool page 262	 RJ45 connectors page 257
		 Industrial Ethernet cordsets page 620

### Technical data

<p><b>Minimum bend radius:</b> - for flexible use: 15 x cable diameter</p> <p><b>Temperature range:</b> - 2170886: -20°C to +60°C - 2170901: -10°C to +70°C - 2170283, 2170284: -5°C to +60°C</p> <p><b>Nominal voltage:</b> (not for power applications) - 2170886: 600V (UL AWM) - 2170284: 1000V - all other P/Ns: 125V</p> <p><b>Characteristic impedance:</b> 100Ω ± 15Ω</p>	<p><b>Color code:</b> - 2170886, 2170901: white, yellow, blue, orange - 2170283, 2170284: white/orange &amp; orange; white/green &amp; green</p> <p><b>Approvals:</b> UL: AWM 21576 (2170284) AWM 21694 (2170886) PLTC (2170886) CMG (2170886) Canada: c(UL) CMG (2170886) cRU AWM I/II A/B FT2 (2170284) Additional: ECOLAB (2170886) RoHS</p>
---	---

Part number	Construction	Stranding	Jacket material	Jacket color	Approvals	Fast connect	PoE	Nominal outer diameter in mm	Approx. weight lbs/mft	SKINTOP® MS-SC PG thread	
<b>CAT.5</b>											
2170886	22 AWG/2pr	7 wire	PVC	green	PROFINET®, UL/CSA CMG, UL AWM, 600V, ECOLAB	yes	yes	0.256	6.5	45	53112210
<b>CAT.5e</b>											
2170901	22 AWG/2pr	7 wire	PVC	black	PROFINET®	no	yes	0.244	6.2	40	53112210
2170283*	26 AWG/2pr	7 wire	halogen-free	teal	—	no	no	0.213	5.4	29	53112210
2170284*	26 AWG/2pr	7 wire	PUR	teal	UL/CSA AWM, 1000V	no	no	0.228	5.8	30	53112210

\* Max cable run: 196 ft (60 m)

PROFINET® is a registered trademark of the PNO (PROFIBUS User Organization). EtherCAT® is a registered trademark of Beckhoff Automation GmbH. Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.