SIEMENS

Data sheet



Pushbutton, 22 mm, round, plastic, green, pushbutton, raised, momentary contact type, with laser labeling, symbol number according to, ISO 7000 or IEC 60417

product brand name	SIRIUS ACT
product designation	Pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Plastic, black, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Raised button
principle of operation of the actuating element	momentary contact type
product extension optional	
light source	No
contact module	Yes
color of the actuating element	green
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	29.5 mm
marking of the actuating element	Customized labeling, graphical symbols acc. to ISO7000 and IEC60417
Front ring	
product component front ring	Yes
design of the front ring	Standard
material of the front ring	plastic
color of the front ring	black
General technical data	
protection class IP	IP66, IP67, IP69(IP69K)
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
	1, 2, 3, 31, 4, 4,, 12, 13
shock resistance	1, 2, 3, 311, 4, 47, 12, 13
shock resistance • acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms
• acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms
acc. to IEC 60068-2-27for railway applications acc. to DIN EN 61373	Sinusoidal half-wave 50g / 11 ms
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373 vibration resistance	Sinusoidal half-wave 50g / 11 ms Category 1, Class B
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373 vibration resistance acc. to IEC 60068-2-6 for railway applications acc. to DIN EN 61373 operating frequency maximum	Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373 vibration resistance acc. to IEC 60068-2-6 for railway applications acc. to DIN EN 61373	Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373 vibration resistance acc. to IEC 60068-2-6 for railway applications acc. to DIN EN 61373 operating frequency maximum	Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h
acc. to IEC 60068-2-27 for railway applications acc. to DIN EN 61373 vibration resistance acc. to IEC 60068-2-6 for railway applications acc. to DIN EN 61373 operating frequency maximum mechanical service life (switching cycles) typical	Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h 10 000 000

 ambient temperature during storage 	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	16.2 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-0BB40-0AA0-Z Y13

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-0BB40-0AA0-Z Y13

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-0BB40-0AA0-Z Y13

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-0BB40-0AA0-Z Y13&lang=en

last modified: 12/21/2020 🖸