



SIMATIC IPC127E; Atom E3940 (4C/4T), 4 GB RAM; Base version 2x Ethernet RJ45, 2x USB3.0; without operating system 64 GB SSD; without mounting accessories

General information	
Product type designation	IPC127E
Installation type/mounting	
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	24 V DC
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	5 ms
Processor	
Processor type	Intel Atom E3940, 1.6 GHz, 4 cores
Drives	
SSD	Yes
Memory	
Type of memory	DDR4
Main memory	4 GB RAM
Capacity of main memory, max.	4 Gbyte
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>Number of PCI slots</li> </ul>	0
Interfaces	
Number of industrial Ethernet interfaces	2; 2x RJ45 (independent)
Number of PROFINET interfaces	2
USB port	2x USB 3.0
Connection for keyboard/mouse	USB / USB
Video interfaces	
<ul style="list-style-type: none"> <li>Graphics interface</li> </ul>	1x DisplayPort
Industrial Ethernet	
<ul style="list-style-type: none"> <li>Industrial Ethernet interface                             <ul style="list-style-type: none"> <li>— 100 Mbps</li> <li>— 1000 Mbps</li> </ul> </li> </ul>	2x Ethernet (RJ45) Yes Yes
Protocols	
Protocols (Ethernet)	
<ul style="list-style-type: none"> <li>TCP/IP</li> </ul>	Yes
Integrated Functions	
Monitoring functions	
<ul style="list-style-type: none"> <li>Temperature monitoring</li> <li>Watchdog</li> <li>Status LEDs</li> </ul>	Yes Yes 1x power, 3x user

• Fan	No
<b>EMC</b>	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity	±6 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high frequency radiation	10 V/m, 80 MHz to 2 GHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2 GHz to 2.7 GHz, 80 % AM acc. to IEC 61000-4-3; 10 V, 10 kHz to 80 MHz, 80 % AM acc. to IEC 61000-4-6
Interference immunity to cable-borne interference	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4; burst); ±0,5 kV (according to IEC 61000-4-5; surge pulse/line to line); ±1 kV (according to IEC 61000-4-5; surge pulse/line to ground)
• Interference immunity on signal cables >30m	±2 kV acc. to IEC 61000-4-5, surge, length > 30 m
• Interference immunity on signal cables < 30m	±1 kV acc. to IEC 61000-4-4; burst; length < 3 m; ±2 kV acc. to IEC 61000-4-4; burst; length > 3 m
Interference immunity to magnetic fields	
• Interference immunity to magnetic fields at 50 Hz	100 A/m; to IEC 61000-4-8
Emission of conducted and non-conducted interference	
• Interference emission via line/AC current cables	EN 61000-6-4:2007 +A1:2011 (industrial environments), EN 61000-6-3:2007 +A1:2011 (residential environments), CISPR 22 Class B, FCC Class A
<b>Degree and class of protection</b>	
IP degree of protection	IP40
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes
Dust protection	Protection against foreign bodies > 1 mm
<b>Ambient conditions</b>	
Ambient temperature during operation	
• Ambient temperature during operation	0 °C up to 55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Relative humidity	5 ... 85 % at 30 °C, no condensation
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	Tested according to IEC 6068-2-6; 5 Hz to 9 Hz: 3.5 mm, 9 Hz to 500 Hz: 9,8 m/s <sup>2</sup>
Shock testing	
• Shock load during operation	Tested according to IEC 60068-2-27: 150 m/s <sup>2</sup> , 11 ms
<b>Operating systems</b>	
pre-installed operating system	No
pre-installed operating system	
• Windows 10 Enterprise	No
<b>Dimensions</b>	
Width	85 mm
Height	85 mm
Depth	41 mm
<b>last modified:</b>	6/2/2022 