SIEMENS

Data sheet

3SU1001-0AA60-0AA0-Z Y11



Illuminated pushbutton, 22 mm, round, plastic, white, pushbutton, flat, latching, Push-to-release mechanism, with laser labeling, upper case

| product brand name | SIRIUS ACT | |
|---|-------------------------------------|--|
| product designation | Illuminated pushbuttons | |
| design of the product | Actuating/signaling element | |
| product type designation | 3SU1 | |
| product line | Plastic, black, 22 mm | |
| Enclosure | | |
| number of command points | 1 | |
| Actuator | | |
| design of the actuating element | Flat button | |
| principle of operation of the actuating element | latching | |
| product extension optional | | |
| light source | Yes | |
| contact module | Yes | |
| color of the actuating element | white | |
| material of the actuating element | plastic | |
| shape of the actuating element | round | |
| outer diameter of the actuating element | 29.5 mm | |
| marking of the actuating element | Any inscription, text in upper case | |
| type of unlocking device | push-to-unlatch mechanism | |
| Front ring | | |
| product component front ring | Yes | |
| design of the front ring | Standard | |
| material of the front ring | plastic | |
| color of the front ring | black | |
| General technical data | | |
| protection class IP | IP66, IP67, IP69(IP69K) | |
| degree of protection NEMA rating | 1, 2, 3, 3R, 4, 4X, 12, 13 | |
| shock resistance | | |
| • acc. to IEC 60068-2-27 | Sinusoidal half-wave 50g / 11 ms | |
| for railway applications acc. to DIN EN 61373 | Category 1, Class B | |
| vibration resistance | | |
| • acc. to IEC 60068-2-6 | 10 500 Hz: 5g | |
| for railway applications acc. to DIN EN 61373 | Category 1, Class B | |
| operating frequency maximum | 1 800 1/h | |
| mechanical service life (switching cycles) typical | 500 000 | |
| reference code acc. to IEC 81346-2 | S | |
| Ambient conditions | | |

ambient temperature during operation ambient temperature during storage -25 ... +70 °C -40 ... +80 °C

environmental category during operation acc. to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %)

| 60721 | |
|-------|--|
| | |

| Installation/ mounting/ dimensions | |
|---|---------|
| height | 29.5 mm |
| width | 29.5 mm |
| shape of the installation opening | round |
| mounting diameter | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm |
| mounting height | 11 mm |
| installation width | 29.5 mm |
| installation depth | 24.3 mm |
| Certificates/ approvals | |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0AA60-0AA0-Z Y11

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-0AA60-0AA0-Z Y11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0AA60-0AA0-Z Y11

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <u>http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0AA60-0AA0-Z Y11&lang=en</u>

last modified:

1/5/2021 🖸