



SIMATIC S7-1500, digital output module DQ 16x230 V AC/1 A ST; TRIAC; 16 channels in groups of 2; 2 A per group; Substitute value: Front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	DQ 16x230VAC/1A ST (Triac)
HW functional status	From FS01
Firmware version	V 1.2.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V13 SP1 / -
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSO</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Integrated operating cycle counter</li> </ul>	Yes; FW V1.2.0 or higher
output voltage / header	
Rated value (AC)	230 V; 120/230 V AC, 50/60 Hz
Power	
Power available from the backplane bus	1.2 W
Power loss	
Power loss, typ.	11.1 W
Digital outputs	
Type of digital output	Triac
Number of digital outputs	16
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	No
<ul style="list-style-type: none"> <li>built-in fuse</li> </ul>	6.3 A melting fuse, slow-blow
Size of motor starters according to NEMA, max.	4
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	1 A

<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	50 W
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L1 (-1.5 V) at maximum output current; L1 (-8.5 V) at minimum output current
<b>Output current</b>	
<ul style="list-style-type: none"> <li>• for signal "1" rated value</li> <li>• for signal "1" permissible range, min.</li> <li>• for signal "1" permissible range, max.</li> <li>• for signal "0" residual current, max.</li> </ul>	1 A 10 mA 15 A; max. 1 AC cycle 2 mA
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> <li>• "1" to "0", max.</li> </ul>	1 AC cycle 1 AC cycle
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for logic links</li> <li>• for uprating</li> <li>• for redundant control of a load</li> </ul>	No No Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> <li>• with inductive load, max.</li> <li>• on lamp load, max.</li> </ul>	10 Hz 0.5 Hz 1 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>• Current per channel, max.</li> <li>• Current per group, max.</li> <li>• Current per module, max.</li> </ul>	1 A; see additional description in the manual 2 A; see additional description in the manual 10 A; see additional description in the manual
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	1 000 m 600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
Substitute values connectable	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> <li>• Maintenance interrupt</li> </ul>	No Yes; maintenance alarm for switching cycle counter
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> <li>• Wire-break</li> <li>• Short-circuit</li> </ul>	No No No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• RUN LED</li> <li>• ERROR LED</li> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Channel status display</li> <li>• for channel diagnostics</li> <li>• for module diagnostics</li> </ul>	Yes; green LED Yes; red LED No Yes; green LED No Yes; red LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels, in groups of</li> <li>• between the channels and backplane bus</li> </ul>	No 2 Yes
<b>Permissible potential difference</b>	
between different circuits	250 V AC between the channels and the backplane bus; 500 V AC between the channels
<b>Isolation</b>	
Isolation tested with	3 100 V DC
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> </ul>	0 °C 60 °C

- vertical installation, min.
- vertical installation, max.

0 °C  
40 °C

#### Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

#### Weights

Weight, approx.	310 g
-----------------	-------

**last modified:**

2/10/2022 