



# Product: <u>9527</u>

High Perform Instr, 27 Pr #22 Str TC, PVC Ins E2, OS, PVC Jkt, PLTC

😭 Request Sample

# **Product Description**

High Performance Instrumentation, 27 Pair 22AWG (7x30) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Industrial Control, Raceways Cable trays and ducts, Digital Control, Instruments (4-20ma, 0-10v,), low voltage digital control (24v,), encoders, control circuits, distributed control
Construction Details	

# Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	27	22	7x30	TC - Tinned Copper

#### Insulation

Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
PVC - Polyvinyl Chloride	0.017 in (0.43 mm)	0.062 in (1.6 mm)	Black, Red and Numbered

## Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	22 AWG (7x30) TC

## Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.063 in (1.6 mm)	0.763 in (19.4 mm)	Yes

# **Electrical Characteristics**

Nom. Conductor DCI	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current		
18.2 Ohm/1000ft	26 pF/ft (85 pF/m)	45 pF/ft (150 pF/m)	2.4 Amps per Conductor at 25°C		
Voltage UL Voltage Rating 300 V (PLTC) Mechanical Characteristics					
Temperature					
UL Temperature	Operating				
105°C -30°C To +105°C					

#### Bend Radius

Stationary Min.	Installation N	lin.	
7.63 in (194 mm)	7.63 in (194 m	וm)	
Max. Pull Tension:		500	lbs (230 kg)

Bulk Cable Weight:

272 lbs/1000ft

 

 Standards and Compliance

 Environmental Suitability:
 Indoor, Outdoor, Sunlight Resistance

 Flammability / Reaction to Fire:
 UL 1685 FT4 loading, FT4, T-29-520, IEEE 1202 FT4

 NEC / UL Compliance:
 Article 725, Article 727, Article 800, CMG, ITC, PLTC

 AWM Compliance:
 AWM 2464

 CEC / C(UL) Compliance:
 CMG

 European Directive Compliance:
 EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)

 APAC Compliance:
 China RoHS II (GB/T 26572-2011)

### History

Update and Revision: Revision Number: 0.534 Revision Date: 04-14-2023

**Part Numbers** 

#### Variants

Item #	Color	UPC
9527 0601000	Chrome	612825254997
9527 060500	Chrome	612825255000

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.