



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d <sub>1</sub>	d <sub>2</sub> Thread	Length l			b	h
20 0.79	M 4	6 0.24	10 0.39	-	9.5 0.37	11 0.43
25 0.98	M 5	10 0.39	16 0.63	25 0.98	11 0.43	13 0.51
32 1.26	M 6	10 0.39	16 0.63	20 0.79	25 0.98	30 1.18
32 1.26	M 8	16 0.63	20 0.79	25 0.98	30 1.18	40 1.57
40 1.57	M 8	16 0.63	25 0.98	40 1.57	-	-
48 1.89	M 8	16 0.63	25 0.98	-	-	-
56 2.20	M 10	20 0.79	30 1.18	-	-	-

Specification

- Wing body  
Plastic  
Technopolymer (Polyamide PA)  
- Glass fiber reinforced  
- Temperature resistant up to 266 °F (130 °C)  
- Black, matte finish
- Threaded stud  
Stainless steel AISI 303
- Plastic Characteristics → page 2135
- Stainless Steel Characteristics → page 2143
- RoHS compliant

Information

Due to their low height EN 531 wing screws offer a comfortable grip for quick two finger clamping applications.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- Wing Screws GN 433 (Stainless Steel) → page 678
- Wing Screws GN 431 (Stainless Steel) → page 679

How to order

EN 531-32-M6-30-NI

- 1 Handle diameter d<sub>1</sub>
- 2 Thread d<sub>2</sub>
- 3 Length l
- 4 Material