


Signal conditioner - PI/NI-2I/I - 5607189

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Product Description

The PI/NI-2I/I current limiter works with two-wire transmitters to prevent short circuit conditions in 4-20 mA loops and is particularly suited for use in hazardous areas. A short circuit condition is indicated by a status LED and each channel has a digital output for reporting to a control system, protected by optocoupler isolation.

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 686822
GTIN	4046356686822
Weight per Piece (excluding packing)	67.000 g
Custom tariff number	85439088
Country of origin	United States

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	27242208
eCl@ss 5.1	27210107
eCl@ss 6.0	27210107
eCl@ss 7.0	27210107
eCl@ss 8.0	27210121
eCl@ss 9.0	27210121

ETIM

ETIM 3.0	EC000310
----------	----------

Signal conditioner - PI/NI-2I/I - 5607189

Classifications

ETIM

ETIM 4.0	EC001485
ETIM 5.0	EC001485
ETIM 6.0	EC001485

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	39121008