



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 60169-17, MIL-PRF-39012, DIN EN 122200

Documents

Assembly instruction 51 M2

Material and plating

Connector parts

| | | | |
|------------------|-----------------|---------|--|
| Center contact | Brass | Plating | AuroDur®, gold plated |
| Outer contact | Brass | | Flash white bronze over silver(e.g. Optargen®) |
| Body | Brass | | Flash white bronze over silver(e.g. Optargen®) |
| Dielectric | PTFE | | |
| Gasket | NeopreneCR 50C6 | | |
| Crimping ferrule | Copper | | Flash white bronze over silver(e.g. Optargen®) |

Electrical data

| | |
|--|--|
| Impedance | 50 Ω |
| Frequency | DC to 10 GHz |
| Return loss | ≥ 31 dB, DC to 1 GHz ≥ 29 dB, 1 to 2 GHz ≥ 20 dB, 2 to 3 GHz |
| Insertion loss | ≤ 0.05 dB, DC to 3 GHz |
| Insulation resistance | ≥ 5 GΩ |
| Center contact resistance | ≤ 1.5 mΩ |
| Outer contact resistance | ≤ 1 mΩ |
| Test voltage | 1500 V rms |
| Working voltage | 500 V rms |
| Power handling (at 20 °C, sea level, VSWR 1.0) | ≤ 80 W @ 2 GHz |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|-----------------------------------|--------------------|
| Mating cycles | ≥ 500 |
| Center contact captivation: axial | ≥ 15 N |
| Coupling test torque | ≤ 1.7 Nm |
| Recommended torque | 0.46 Nm to 0.69 Nm |

Environmental data

| | |
|---------------------|--------------------------------------|
| Temperature range | -65 °C to +165 °C |
| Thermal shock | MIL-STD-202, Method 107, Condition B |
| Corrosion | MIL-STD-202, Method 101, Condition B |
| Vibration | MIL-STD-202, Method 204, Condition B |
| Shock | MIL-STD-202, Method 213, Condition G |
| Moisture resistance | MIL-STD-202, Method 106 |
| RoHS | compliant |

Tooling

| | |
|---------------|------------|
| Crimping tool | 11W150-000 |
| Crimp insert | 11W150-102 |

Suitable cables

RG 316 /U-d, K02252d

Weight

| | |
|--------|------------|
| Weight | 21.7 g/pce |
|--------|------------|

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-------------|----------|------|---------------------------|--|---------------|
| Inge Mühlauer | 10.08.04 | Chr. Janßen | 02.02.21 | e00 | 20-1927 | S. Huber-Siegl | 02.02.21 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.com | | | | | | Tel. : +49 8684 18-0 Email : info@rosenberger.com | |
| | | | | | | | Page 2 / 2 |