



Main

| | |
|-------------------------------|---|
| Range of Product | Telemecanique Safety switches XCS |
| Product or Component Type | Guard switch |
| Component name | XCSPR |
| Material | Plastic |
| Head type | Turret head rotary axis |
| Insulation | Double insulated |
| Type of operator | Spindle 30 mm |
| Electrical Connection | Terminal |
| Contacts type and composition | 1 NC + 1 NC |
| Contact operation | Slow-break |
| Clamping connection capacity | 1 x 0.5...2 x 1.5 mm ² with or without cable end |
| Cable entry | 1 entry tapped 1/2" NPT |
| Number of poles | 2 |

Complementary

| | |
|--|--|
| Cable outer diameter | 0.28...0.39 in (7...10 mm) |
| Positive opening | With NC contact |
| Tripping angle | 5 ° |
| Mechanical durability | 1000000 cycles |
| Minimum torque for tripping | 0.89 lbf.in (0.1 N.m) |
| Positive opening minimum torque | 2.21 lbf.in (0.25 N.m) |
| Contact code designation | A300, AC-15 (Ue = 120 V, Ie = 6 A)EN/IEC 60947-5-1 A300, AC-15 (Ue = 240 V, Ie = 3 A)EN/IEC 60947-5-1 Q300, DC-13 (Ue = 125 V, Ie = 0.55 A)EN/IEC 60947-5-1 Q300, DC-13 (Ue = 250 V, Ie = 0.27 A)EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 VUL 508 300 VCSA C22.2 No 14 500 V 3)EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 6 kV EN/IEC 60947-5-1 |
| Maximum resistance across terminals | 30 mOhm EN/IEC 60947-5-4 |
| Short-circuit protection | 10 A cartridge fuse gG (gl) |
| Safety level | Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach SIL 3 with the appropriate monitoring system and correctly wired IEC 61508 |
| Safety reliability data | B10d = 5000000 value given for a life time of 20 years limited by mechanical or contact wear |
| Enclosure Material | Polyamide PA66 fibre glass impregnated |
| Lever material | Stainless steel |
| Width | 1.18 in (30 mm) |
| Height | 4.33 in (110 mm) |
| Depth | 2.36 in (60 mm) |
| Net Weight | 0.26 lb(US) (0.12 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60204-1 EN/IEC 60947-5-4 CSA C22.2 No 14 UL 508 EN 1088/ISO 14119 EN/ISO 12100 EN/IEC 60947-5-1 |
| Product Certifications | CSA UL BG |
| Protective treatment | TC TH |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 50 gn 10...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn 11 ms IEC 60068-2-27 |
| Electrical shock protection class | Class II EN/IEC 61140 |
| IP degree of protection | IP67 conforming to IEC 60529 |

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 22411 - LIMIT SWITCHES,IEC,XCKJ |
| Discount Schedule | T |
| GTIN | 3389110177169 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.23 oz (120 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.77 in (4.5 cm) |
| Package 1 width | 2.60 in (6.6 cm) |
| Package 1 Length | 4.13 in (10.5 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 20 |
| Package 2 Weight | 6.29 lb(US) (2.855 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
