

Data sheet for Line reactor

MLFB-Ordering data

6SE6400-3CC00-6AD3



Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input

| | |
|------------------|---------------|
| Number of phases | 3 AC |
| Line voltage | 200 ... 480 V |

Output

| | |
|---------------|-------|
| Rated current | 4.8 A |
|---------------|-------|

Mechanical data

Dimensions

| | |
|----------------------|---------------------|
| Width | 75.5 mm (3.0 in) |
| Height | 200.0 mm (7.9 in) |
| Depth | 50.0 mm (2.0 in) |
| Degree of protection | IP20 / UL open type |
| Net weight | 1.4 kg (3.1 lb) |

Connections

Line side

| | |
|-------------------------|---|
| Version | screw-type terminal |
| Conductor cross-section | 1.00 ... 2.50 mm ² (18 ... 14 AWG) |

Load side

| | |
|-------------------------|-------------------------------|
| Version | Pigtail |
| Conductor cross-section | 1.50 mm ² (16 AWG) |
| Cable length | 0.37 m (1.21 ft) |

PE connection

| | |
|---------|---------|
| Version | M5 stud |
|---------|---------|

Standards

| | |
|---------------------------|-------|
| Compliance with standards | cURus |
|---------------------------|-------|