



Main

Range	Thalassa
Product name	Thalassa PLS
Device short name	PLS
Enclosure type	Multi-purpose
Category	Insulating modular rear
Nominal height	14.17 in (360 mm)
Nominal width	28.35 in (720 mm)
Nominal depth	5.31 in (135 mm)
Enclosure mounting	Wall mounted
Device composition	1 rear part on enclosure
Body type	One piece moulded
Type of front cover	Without

Complementary

Material	Polyester reinforced with fibreglass
Color	Body Gray RAL 7035)
Standards	NEMA 4X IEC 62208 NEMA classification 13
Product Certifications	UL

Environment

Electrical Insulation Class	Class II
IP degree of protection	IP66 IEC 60529
IK degree of protection	IK09 IEC 62262
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Storage	-22...158 °F (-30...70 °C)

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480774034
Nbr. of units in pkg.	1
Package weight(Lbs)	6.59 lb(US) (2.991 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.51 in (14 cm)
Package 1 width	14.17 in (36 cm)
Package 1 Length	28.35 in (72 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	3
Package 2 Weight	21.91 lb(US) (9.939 kg)
Package 2 Height	14.76 in (37.5 cm)

Package 2 width	16.93 in (43 cm)
Package 2 Length	28.54 in (72.5 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile