HellermannTyton

Specification Sheet

Part Number: TAG62L-788



White polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.

LaserTags are sheet fed for easy loading and fast printing.

Laser Tag Label, 1.5" x .37", 125 Per Sheet, PET, White, 1000/pkg

Article Number 594-62788

Type TAG62L

Color White (WH)

Quantity Per pack

Product Description

HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking.

Short Description Laser Tag Label, 1.5" x .37", 125 Per Sheet, PET, White, 1000/pkg

| Global | D ~ | N I |
|--------|-----|------|
| CHONAI | Рап | Name |

TAG62L-788-WH

Width W (Imperial)

1.5

Width W (Metric)

38.1

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.50

Thickness T (Metric)

64.0

Height H (Imperial)

0.375

Height H (Metric)

9.52

Material

Type 788, Polyester (788)

Material Shortcut

788

Adhesive

Acrylic

Halogen Free

No

UV Resistant (Yes/No)

No

Adhesive Operating Temperature

-40°F to +199°F (-40°C to +93°C)

Operating Temperature

-40°F to +199°F (-40°C to +93°C)

| Reach Compliant (Article 33) | Yes |
|------------------------------|------------|
| ROHS Compliant | Yes |
| | |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3919905060 |
| Labels per Column | 25 |
| Labels per Row | 5 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions