HellermannTyton

Specification Sheet

Part Number: TAG33T1-DTH



White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Labels, 3.0" x 2.0", 1 Across, PET, White, 1000/roll

Article Number 596-00039

Type TAG33T1

Color White (WH)

Quantity Per roll

Product Description

HellermannTyton white polyolefin labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's polyolefin material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Short Description Thermal Transfer Labels, 3.0" x 2.0", 1 Across, PET, White, 1000/roll

Clobal	Dort	Nama
Global	Pan	name

TAG33T1-PO-WH

Width W (Imperial)

3.0

Width W (Metric)

76.2

Thickness T (Metric)

64.0

Height H (Imperial)

2.0

Height H (Metric)

50.8

Width of Liner (Metric)

78.74

Width of Liner (Imperial)

3.10

Material

Polyolefin (PO)

Material Shortcut

PO

Adhesive

Acrylic

Halogen Free

No

UV Resistant (Yes/No)

No

Adhesive Operating Temperature

-40°F to +302°F (-40°C to +150°C)

Operating Temperature

-40°F to +140°F (-40°C to +60°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions