

Specification Sheet

Part Number: 596-00666



Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 10/pkg

Article Number 596-00666

Type CBACKFED10

Color Yellow (YE)

Quantity Per pack

Product Description

HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.

Short Description

Solar Label, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x

.75", VL, Yellow, 10/pkg

Global Part Name

CBACKFED10-443/281-YE

Local Order Number 2

Cross Reference = 50 per roll: 596-00587; Metal Solar Placard 5 pack:

596-00834; Spanish version 50 per roll: 596-00827

Width W (Imperial)

4.12

Width W (Metric)

104.60

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

0.75

Height H (Metric)

19.05

Material	Type 443/281, UV stabilized, flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	Yes
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33) ROHS Compliant	Yes
Certification/Specification	NEC2017 NEC2020 NEC2014 UL 969
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060

1

Labels per Column

