

## **Specification Sheet**

Part Number: 596-00810

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

**DESCONECTADOR SOLAR** 

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Reflective, Spanish, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/roll

Article Number 596-00810

Type SOLARDS

Color Red (RD)

Quantity Per roll

Product Description HellermannTyton Pre-Printed Solar Installation Labels are designed to

meet the requirements of the National Electrical Code® (NEC®) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder-coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No	Short Description	Solar Label, Reflective, Spanish, SOLAR DISCONNECT, 6.5" x 1.0" VL, Red, 50/roll
Width W (Imperial) 6.5  Width W (Metric) 165.1  Thickness T (Imperial) 0.0025  Thickness T (Metric) 64.0  Height H (Imperial) 1.0  Height H (Metric) 25.4  Material Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No	Global Part Name	SOLARDS-505/281-RD
Width W (Metric)  Thickness T (Imperial)  0.0025  Thickness T (Metric)  64.0  Height H (Imperial)  1.0  Height H (Metric)  25.4  Material  Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut  505/281  Adhesive  Acrylic  Halogen Free  No	Local Order Number 2	English Version: 596-00246
Width W (Metric)  Thickness T (Imperial)  0.0025  Thickness T (Metric)  64.0  Height H (Imperial)  1.0  Height H (Metric)  25.4  Material  Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut  505/281  Adhesive  Acrylic  Halogen Free  No		
Thickness T (Imperial)  O.0025  Thickness T (Metric)  64.0  Height H (Imperial)  1.0  Height H (Metric)  25.4  Material  Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut  505/281  Adhesive  Acrylic  Halogen Free  No	Width W (Imperial)	6.5
Thickness T (Metric) 64.0  Height H (Imperial) 1.0  Height H (Metric) 25.4  Material Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No	Width W (Metric)	165.1
Height H (Imperial)  Height H (Metric)  25.4  Material  Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut  505/281  Adhesive  Acrylic  Halogen Free  No	Thickness T (Imperial)	0.0025
Height H (Metric)  25.4  Material  Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut  505/281  Adhesive  Acrylic  Halogen Free  No	Thickness T (Metric)	64.0
Material Type 505/281, UV-stabilised, reflective vinyl with clear polyes laminate (505/281)  Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No	Height H (Imperial)	1.0
Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No	Height H (Metric)	25.4
Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No		
Material Shortcut 505/281  Adhesive Acrylic  Halogen Free No		
Adhesive Acrylic Halogen Free No	Material	Type 505/281, UV-stabilised, reflective vinyl with clear polyester laminate (505/281)
Halogen Free No	Material Shortcut	505/281
	Adhesive	Acrylic
	Halogen Free	No
UV Resistant (Yes/No) Yes	UV Resistant (Yes/No)	Yes

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C) -40°F to +174°F (-40°C to +79°C) **Operating Temperature** Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Certification/Specification NEC2011 UL Recognized (US) Yes Package Quantity (Imperial) 50 Package Quantity (Metric) 50 3919102055 Customs Number 1 Labels per Column

1

## About HellermannTyton

Labels per Row

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).