

Specification Sheet

Part Number: 596-00857

Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure

Aggressive adhesive ensures strong bond, even on powder coated surfaces

Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability

Optional Paint Shields provide additional protection for pre-printed and variable data placards



Metal Solar Placard, Engravable, PHOTOVOLTAIC AC DISCONNECT, 3.75"x1.0", AA, Black, 5/pkg

Article Number 596-00857

Type ACDISCTM5ENG

Color Black (BK)

Quantity Per pack

Product Description Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.

Short Description	Metal Solar Placard, Engravable, PHOTOVOLTAIC AC DISCONNECT, 3.75"x1.0", AA, Black, 5/pkg
Global Part Name	ACDISCTM5ENG-AA-BK
Local Order Number 2	Cross Reference = Paint Shield: 596-00796
Length L (Imperial)	3.75
Length L (Metric)	95.25
Width W (Imperial)	3.75
Width W (Metric)	92.25
Height H (Imperial)	1.0
Height H (Metric)	25.40
Material	Anodized Aluminum (AA)
Material Shortcut	AA
Adhesive	Ultra High Bond Permanent Acrylic Adhesive
Halogen Free	No
UV Resistant (Yes/No)	No

Adhesive Operating Temperature	from +50°F (from +10°C)
Operating Temperature	-40°F to +203°F (-40°C to +95°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2017 NEC2014
Warranty (US)	Yes
Package Quantity (Imperial)	5
Package Quantity (Metric)	5
Customs Number	8310000000
Labels per Column	1
Labels per Row	1

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

