XUYFVERMD101

Photoelectric sensors XU, glass fibre optic for sensor, thru beam, straight, metal, 1 m, Sn200mm



Main

Mani	
Range of Product	Telemecanique Photoelectric sensors XU
Sensor name	XUY
Sensor design	Fiber design
Sheath type	Metal reinforced
[Sn] nominal sensing distance	7.87 in (200 mm) XUYAFV
End fitting type	Straight nickel plated brass, M4 x 0.7

Complementary

Electronic sensor type	Photo-electric sensor	
Optic fiber material	50 μ glass	
Sheath material	Spiraled metal + polyolefine	
Detection system	Thru beam	
Optic fiber length	3.28 ft (1 m)	
Minimum bending radius	0.79 in (20 mm)	
Head mounting	M4 x 0.7	

Environment

Ambient Air Temperature for Operation	-13248 °F (-25120 °C)	
---------------------------------------	-----------------------	--

Ordering and shipping details

Category	22481-SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	3389119008198
Nbr. of units in pkg.	1
Package weight(Lbs)	1.94 oz (55.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	6.69 in (17 cm)	
Package 1 width	0.59 in (1.5 cm)	
Package 1 Length	6.69 in (17 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes

Warranty	18 months