

SIMATIC IFP1900 Flat Panel 19" display (16: 9), Touch, Standard up to 5 m, 1366x 768 pixels, for 24 V DC, display port/DVI interface incl. DVI/USB cable 1.8 m



General information	
Product type designation	IFP1900
Short designation	Flat Panel 19" touch
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	18.5 in; 19"
Screen diagonal [cm]	47 cm
Display width	409.8 mm
Display height	230.4 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	170° x 160°
Resolution (pixels)	
<ul style="list-style-type: none"> • Image resolution • Horizontal image resolution • Vertical image resolution • Pixel size, horizontal • Pixel size, vertical 	1 366 x 768 1 366 pixel 768 pixel 0.3 mm 0.3 mm
General features	
<ul style="list-style-type: none"> • Brightness/contrast • Detachable from computer unit • Luminance 	300 cd/m ² / 1 000:1 5 m 300 cd/m ²
Backlighting	
<ul style="list-style-type: none"> • Type of backlighting • MTBF backlighting (at 25 °C) • Backlight dimmable 	LED 50 000 h; At 25°C Yes; 0-100 %
Control elements	
Control elements	single-touch screen
Input device	
<ul style="list-style-type: none"> • Integrated mouse cursor control 	No
Touch operation	
<ul style="list-style-type: none"> • Design as touch screen • Monitor keyboard 	Yes; Analog-resistive Yes
Installation type/mounting	
Design	Built-in unit
Front mounting	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	35°
maximum permitted backward tilt angle from vertical	35°

Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss, typ.	40 W
Power loss, max.	65 W
Interfaces	
Video interfaces	
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4 at the front	Yes
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes
Use in hazardous areas	
• FM Class I Division 2	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C; Vertical installation (horizontal)
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; no condensation
Vibrations	
• Vibration load in operation	10 m/s ²
• Vibration load during transport/storage	10 m/s ²
Shock testing	
• Shock load during operation	150 m/s ²
• shock acceleration during storage/transport	150 m/s ²
Mechanics/material	
Enclosure material (front)	
• Aluminum	Yes
Dimensions	
Width of the housing front	483 mm
Height of housing front	337 mm
Mounting cutout, width	465 mm; Tolerance: +1 mm
Mounting cutout, height	319 mm; Tolerance: +1 mm
Overall depth	62.5 mm
Weights	
Weight (without packaging)	5.5 kg
Weight (with packaging)	6.5 kg
last modified:	12/16/2020 