

# Adapters / Cable Assemblies



**628 - 000 - 924**

Series

Internal

Product Type

## FEATURES

- DVI - analog to 15 pin VGA adapter
- High cycle, dual beam low insertion force contacts
- D-subminiature adapting end is polarized
- Fully shielded to protect against EMI/RFI
- 4-40 threaded insert with thumbscrew
- Available in both long and short versions

## SPECIFICATIONS

- Insulator material: Thermoplastic polyester, UL94V-0 rated
- Shell material: Nickel or tin/lead plated steel
- Current rating: 1.5 amperes
- Dielectric withstanding voltage: 500V for 10 milliseconds
- Insulation resistance: 100 M ohms at 100VDC
- Voltage: 40V
- Impedance: 75 Ohms +/- 10% on co-axial wires

## PRODUCT TYPE

921	DVI/HD15 cable assembly
922	LFH60/HD15 cable assembly
923	LFH60/DVI cable assembly
924	DVI/HD15 adapter
924S	DVI/HD15 adapter – short black
924W	DVI/HD15 adapter – short white
932	USB A/USB B cable assembly
935	RJ11 cable assembly
936	RJ45 cable assembly
937	SMB/SMB cable assembly
940	USB A/mini USB B cable assembly
944	USB B/USB B cable assembly
945	BNC/SMB cable assembly
953	Serial internal cable assembly
954	Multiple video cable assembly
955	LFH60/6XBNC cable assembly
957	LFH60/4XSCART cable assembly

\*For a more complete listing of products, please contact [edac@edac.net](mailto:edac@edac.net)



FOR MORE INFORMATION VISIT [www.edac.net](http://www.edac.net) OR EMAIL [edac@edac.net](mailto:edac@edac.net)

Phone: 416-754-3322

Fax: 416-754-3299