



- 2 Type**
- A Mounting with hex head screw
  - B Mounting with countersunk screw

**Metric table**



Dimensions in: millimeters - inches

$l_1$	$l_2 \pm 0.5$	$l_3$	$b_1$	$b_2$	$d$	$h_1$	$h_2$	$h_3$	$h_4$	$t$
114	93.5	74	35	19	6.5	33	7	11	9	5
4.49	3.68	2.91	1.38	0.75	0.26	1.30	0.28	0.43	0.35	0.20

**Specification**



- Plastic  
Technopolymer (Polyamide PA)  
- Glass fiber reinforced  
- Temperature resistant up to 230 °F (110 °C)  
- Black-gray, similar to RAL 7021, matte finish
- Color of the cover (shiny finish):
  - Black-gray, RAL 7021
  - Orange, RAL 2004
  - Gray, RAL 7035
  - Yellow, RAL 1021
  - Blue, RAL 5024
  - Red, RAL 3000
  - Green, RAL 6017
- Strength Values → page 2081
- Plastic Characteristics → page 2135
- RoHS compliant

- DSG
- DOR
- DGR
- DGB
- DBL
- DRT
- DGN

**Information**

When using guards on machines and automation systems, which include double hinged doors, the EN 630 off-set “U” handles completely enclosed are a safety element for operator fingers while the doors are being used. Use of a colored safety cover makes identification easier.

Resistant to solvents, oils, grease and other chemical agents.

The cover is included but supplied unassembled.

see also...

- Product Family Ergostyle® → page 18
- Product Family Standard Parts for Profile Systems → page 18
- T-Nut Assemblies GN 965 (for 30 / 40 mm T-Slot Profile Systems) → page 2048
- T-Nut Assemblies GN 968 (for 30 / 40 / 45 mm T-Slot Profile Systems) → page 2058

How to order	
1	Length $l_1$
2	Type
3	Color of the cover

**EN 630-114-B-DOR**