



SS Stainless Steel

2 Type

- A Without dowel pin hole
- B* With dowel pin hole

Metric table



Dimensions in: millimeters - inches

d ₁ Thread	d ₃	d ₄	d ₅ H11	e	h	k	Length l
M 5	14 .55	20 .79	1.5 .06	2.5 .10	12 .47	8 .31	7 .28
M 6	16 .63	24 .94	1.5 .06	2.5 .10	14 .55	10 .39	8 .31
M 8	20 .79	30 1.18	2 .08	3 .12	17 .67	12 .47	10 .39
M 10	28 1.10	36 1.42	3 .12	4 .16	20 .79	14 .55	12 .47
M 12	32 1.26	40 1.57	4 .16	4 .16	24 .94	16 .63	16 .63

* Not available from stock, requires a minimum order quantity

Specification



- Stainless steel **NI**
European Standard No. 1.4305 (AISI 303)
Matte shot-blasted finish

- RoHS compliant

Information

DIN 6303 knurled nuts are machined from solid bar.

The dowel pin hole d₅ in the nut is designed for securing the nut onto a shaft with a dowel or groove pin.

see also...

- Knurled Nuts GN 536 (Stainless Steel)
- Knurled Nuts DIN 466 (Stainless Steel)

How to order DIN 6303-M6-A-NI	1 Thread d ₁
	2 Type
	3 Material