



SS Stainless Steel

**Metric table**

2 3 4

Dimensions in: millimeters - inches

| d <sub>1</sub> | d <sub>2</sub><br>Thread | Length l ≈      |            |            |            |            |            |                      |            |            |            |            |            |            | d <sub>3</sub> | h <sub>1</sub> | h <sub>2</sub> |            |            |            |            |
|----------------|--------------------------|-----------------|------------|------------|------------|------------|------------|----------------------|------------|------------|------------|------------|------------|------------|----------------|----------------|----------------|------------|------------|------------|------------|
|                |                          | GN 6335.4<br>ST |            |            |            |            |            | GN 6335.5<br>ST / SK |            |            |            |            |            |            |                |                |                |            |            |            |            |
| 32<br>1.26     | M 6                      | 16<br>0.63      | 20<br>0.79 | 25<br>0.98 | 30<br>1.18 | 35<br>1.38 | 45<br>1.77 | 16<br>0.63           | 20<br>0.79 | 25<br>0.98 | 30<br>1.18 | 35<br>1.38 | 45<br>1.77 | 10<br>0.39 | 16<br>0.63     | 20<br>0.79     | 25<br>0.98     | 30<br>1.18 | 14<br>0.55 | 20<br>0.79 | 10<br>0.39 |
| 40<br>1.57     | M 8                      | 16<br>0.63      | 20<br>0.79 | 25<br>0.98 | 30<br>1.18 | 40<br>1.57 | 55<br>2.17 | 15<br>0.59           | 20<br>0.79 | 25<br>0.98 | 30<br>1.18 | 40<br>1.57 | 55<br>2.17 | 20<br>0.79 | 25<br>0.98     | 30<br>1.18     | 40<br>1.57     | -          | 18<br>0.71 | 25<br>0.98 | 13<br>0.51 |
| 50<br>1.97     | M 10                     | 25<br>0.98      | 30<br>1.18 | 35<br>1.38 | 45<br>1.77 | 55<br>2.17 | -          | 25<br>0.98           | 30<br>1.18 | 35<br>1.38 | 45<br>1.77 | 55<br>2.17 | -          | 20<br>0.79 | 25<br>0.98     | 30<br>1.18     | 45<br>1.77     | 55<br>2.17 | 22<br>0.87 | 32<br>1.26 | 20<br>0.79 |
| 63<br>2.48     | M 12                     | 30<br>1.18      | 35<br>1.38 | 40<br>1.57 | 50<br>1.97 | 60<br>2.36 | -          | 30<br>1.18           | 35<br>1.38 | 40<br>1.57 | 50<br>1.97 | 60<br>2.36 | -          | 30<br>1.18 | 40<br>1.57     | 50<br>1.97     | -              | -          | 26<br>1.02 | 40<br>1.57 | 25<br>0.98 |
| 80<br>3.15     | M 16                     | -               | -          | -          | -          | -          | -          | 30<br>1.18           | 40<br>1.57 | 50<br>1.97 | 60<br>2.36 | 70<br>2.76 | -          | -          | -              | -              | -              | -          | 35<br>1.38 | 50<br>1.97 | 30<br>1.18 |

**Specification**

1

**GN 6335.4**

- Hand knob  
Plastic  
Technopolymer (Polyamide PA) **ST**  
Shock-resistant, black, matte finish
- Hand knob  
Plastic  
Duroplast (Phenolic PF) **SK**  
Black, shiny finish
- Threaded stud  
Steel, zinc plated, blue passivated finish

**GN 6335.5**

- Hand knob  
Plastic  
Technopolymer (Polyamide PA) **ST**  
Shock-resistant, black, matte finish
- Threaded stud  
Stainless steel  
M6 - M10:  
European Standard No. 1.4567 (AISI 304 Cu)  
M12:  
European Standard No. 1.4305 (AISI 303)
- Hand knob  
Plastic  
Duroplast (Phenolic PF) **SK**  
Black, shiny finish
- Threaded stud  
Stainless steel A2

• RoHS compliant

**Information**

GN 6335.4 and GN 6335.5 hand knobs comply with DIN 6335 type L.

see also...

- Hand Knobs GN 6335.4 / GN 6335.5 with Loss Protection GN 111.7

**On request**

- Special inch and metric size threaded studs and stud lengths

How to order (Steel threaded stud)

GN 6335.4-SK-80-M16-50

- 1 Material
- 2 Handle diameter d<sub>1</sub>
- 3 Thread d<sub>2</sub>
- 4 Length l

How to order (Stainless steel threaded stud)

GN 6335.5-ST-50-M10-25

- 1 Material
- 2 Handle diameter d<sub>1</sub>
- 3 Thread d<sub>2</sub>
- 4 Length l