# NSYS3CM304020

HMI encl. Spacial S3CM. H300xW400xD200IP54 IK10, RAL7035.Rear door.





# Main

Range	Spacial
Product name	Spacial S3CM
Application	Human-machine dialogue application
Category	Control enclosure
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	15.75 in (400 mm)
Enclosure nominal depth	7.87 in (200 mm)
Installation accessory type	Suspension system
Product destination	Interface
Device composition	1 body 1 door with lock 2 rail 1 reinforcement plate 1 front trim frame

# Complementary

Body type	Single piece body	
Door type	Solid	
Number of doors	Rear 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Rear	
Removable parts	Door by hinges Trim frame by screws 2 rails by screws	
Material	Enclosure and front face steel Trim frame aluminium	
Surface finish	Epoxy-polyester powder	
Color	Enclosure Gray RAL 7035) Front face Gray RAL 7040)	
Net Weight	20.16 lb(US) (9.146 kg)	

#### Environment

IP degree of protection	IP54 IEC 60529
IK degree of protection	IK10 IEC 62262

# Ordering and shipping details

80033-ENCLOSURE SYSTEMS POLYESTER	
ES1	
3606480212932	
1	
20.16 lb(US) (9.146 kg)	
	ES1 3606480212932 1

Returnability	No
Country of origin	ES
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	12.60 in (32.0 cm)
Package 1 width	16.54 in (42.0 cm)
Package 1 Length	8.66 in (22.0 cm)
Offer Sustainability Sustainable offer status REACh Regulation	Green Premium product
	= REMOTI Beolaration
REACh free of SVHC	Yes
REACh free of SVHC EU RoHS Directive	
	Pro-active compliance (Product out of EU RoHS legal scope) <sup>™</sup> EU RoHS
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

# Contractual warranty

Environmental Disclosure

Warranty	18 months

Product Environmental Profile