

SITOP MODULAR/1AC/24VDC/20A/CO

*** spare part *** SITOP modular plus 20 A Stabilized power supply input: 120/230 V AC, output: 24 V DC/20 A Option for with protective varnish



Figure similar

Input	
type of the power supply network	1-phase and 2-phase AC
supply voltage at AC	Set by means of wire jumper on the device; starting from $V_{in} > 93/183$ V
<ul style="list-style-type: none"> initial value 	
supply voltage	120 V 230 V
<ul style="list-style-type: none"> 1 at AC rated value 2 at AC rated value 	
input voltage	85 ... 132 V 176 ... 264 V
<ul style="list-style-type: none"> 1 at AC 2 at AC 	
design of input wide range input	No
overvoltage overload capability	$2.3 \times V_{in}$ rated, 1.3 ms
operating condition of the mains buffering	at $V_{in} = 230$ V
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at $V_{in} = 230$ V
line frequency	50 Hz 60 Hz
<ul style="list-style-type: none"> 1 rated value 2 rated value 	
line frequency	47 ... 63 Hz
input current	7.7 A 3.5 A
<ul style="list-style-type: none"> at rated input voltage 120 V at rated input voltage 230 V 	
current limitation of inrush current at 25 °C maximum	60 A
I ² t value maximum	9.9 A ² ·s
fuse protection type	Yes
<ul style="list-style-type: none"> in the feeder 	Recommended miniature circuit breaker at 1-phase operation: 10 A characteristic C; required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2411-1JA10 (120 V) or 3RV2411-1FA10 (230 V)
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	24 V
<ul style="list-style-type: none"> at output 1 at DC rated value 	
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	0.1 % 0.1 %
<ul style="list-style-type: none"> on slow fluctuation of input voltage 	
<ul style="list-style-type: none"> on slow fluctuation of ohm loading 	

residual ripple	
• maximum	100 mV
• typical	30 mV
voltage peak	
• maximum	200 mV
• typical	60 mV
adjustable output voltage	24 ... 28.8 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer
display version for normal operation	Green LED for 24 V OK
type of signal at output	via signaling module (6EP1961-3BA10)
behavior of the output voltage when switching on	Overshoot of Vout approx. 3 %
response delay maximum	0.1 s
voltage increase time of the output voltage	
• typical	50 ms
output current	
• rated value	20 A
• rated range	0 ... 20 A; +60 ... +70 °C: Derating 3.5%/K
supplied active power typical	480 W
short-term overload current	
• at short-circuit during operation typical	60 A
duration of overloading capability for excess current	
• at short-circuit during operation	25 ms
constant overload current	
• on short-circuiting during the start-up typical	23 A
product feature	
• bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	89 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	59 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	2 %
setting time	
• load step 50 to 100% typical	2 ms
• load step 100 to 50% typical	2 ms
setting time	
• maximum	5 ms
Protection and monitoring	
design of the overvoltage protection	< 35 V
response value current limitation typical	23 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 23 A or latching shutdown
enduring short circuit current RMS value	
• typical	23 A
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown"
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.4 mA
protection class IP	IP20

Approvals	
certificate of suitability <ul style="list-style-type: none"> • CE marking • UL approval • CSA approval • cCSAus, Class 1, Division 2 • ATEX 	Yes Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 No No
certificate of suitability <ul style="list-style-type: none"> • IECEx • NEC Class 2 • ULhazloc approval • FM registration 	No No No No
type of certification CB-certificate	No
certificate of suitability <ul style="list-style-type: none"> • EAC approval 	Yes
certificate of suitability shipbuilding approval	No
shipbuilding approval	-
Marine classification association <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) 	No No No No No
EMC	
standard <ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	EN 55022 Class B EN 61000-3-2 EN 61000-6-2
environmental conditions	
ambient temperature <ul style="list-style-type: none"> • during operation • during transport • during storage 	0 ... 70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • at input • at output • for auxiliary contacts 	screw-type terminals L, N, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.5 ... 4 mm ² -
width of the enclosure	160 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
net weight	2.2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Buffer module, signaling module
MTBF at 40 °C	786 164 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

