

## METRIC MEASUREMENT VERSION

76102WS Multi-Conductor - 300V Foil/Spiral Shield, Continuous Flexing Data Applications Up to 6 Million Flex Life Cycles



For more Information  
please call

1-800-Belden1

### General Description:

26 AWG stranded (7x33) tinned copper conductors, PVC insulation, Aluminum/Polyester Foil Shield, Tinned copper spiral shield, 90% coverage, oil-resistant PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material
2	26	7x34	TC - Tinned Copper

#### Insulation

##### Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.254

##### Insulation Color Code Chart:

Number	Color
1	Black
2	Red

#### Outer Shield

##### Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Tape	Aluminum/Mylar	100.000
2	Serve	TC - Tinned Copper	90.000

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.016

#### Overall Cable

Overall Nominal Diameter: 4.623 mm

### Mechanical Characteristics (Overall)

Bulk Cable Weight: 31.252 Kg/Km

Max. Recommended Pulling Tension: 37.810 N

Min. Bend Radius/Minor Axis: 38.100 mm

Min. Bend/Installation: 38.100 mm

Min. Bend Radius (Continuous Flexing): 38.100 mm

Flex Cycle Rating: 6 Million Flexes

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

MII Order #39 (China RoHS): Yes

Customer Part Number Reference Specification: AWM/STYLE 10002, AWM/STYLE 2661, CSA AWM I/II A/B, EU Directive 2011/65/EU(RoHS2), REACH Regulation (EC 1907/2006), California Proposition 65

## METRIC MEASUREMENT VERSION

76102WS Multi-Conductor - 300V Foil/Spiral Shield, Continuous Flexing Data Applications Up to 6 Million Flex Life Cycles

### Flame Test

CSA Flame Test: FT4

### Suitability

Suitability - Burial: Yes

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
62.000

### Nom. Inductance:

Inductance (µH/m)
0.656

### Nom. Capacitance Conductor to Conductor:

Freq. (MHz)	Capacitance (pF/m)
0.001	101.711

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
134.521

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
25.264

### Max. Operating Voltage - UL:

Voltage
300V

## Notes (Overall)

**Notes:** Temperature Range -10 to 105°C(static), +5 to 105°C (dynamic)

## Put Ups and Colors:

No put ups and colors are available for this product

Revision Number: 0    Revision Date: 09-27-2017

© 2020 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.