SIEMENS

Data sheet



Pushbutton, 22 mm, round, plastic, green, Front ring, raised, castellated momentary contact type, with laser labeling, lower case $\frac{1}{2} \frac{1}{2} \frac{$

| and door to be and a some | OIDILIO A OT |
|--|---|
| product brand name | SIRIUS ACT |
| product designation | Pushbuttons |
| design of the product | Actuating/signaling element |
| product type designation | 3SU1 |
| product line | Plastic, black, 22 mm |
| Enclosure | |
| number of command points | 1 |
| Actuator | |
| design of the actuating element | Flat button |
| principle of operation of the actuating element | momentary contact type |
| product extension optional | |
| • light source | No |
| contact module | Yes |
| color of the actuating element | green |
| material of the actuating element | plastic |
| shape of the actuating element | round |
| outer diameter of the actuating element | 29.5 mm |
| marking of the actuating element | Customized labeling, text in lower case letters |
| Front ring | |
| | |
| product component front ring | Yes |
| product component front ring design of the front ring | Yes high with crenellations |
| | |
| design of the front ring | high with crenellations |
| design of the front ring material of the front ring | high with crenellations plastic |
| design of the front ring material of the front ring color of the front ring | high with crenellations plastic |
| design of the front ring material of the front ring color of the front ring General technical data | high with crenellations plastic black |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP | high with crenellations plastic black IP66, IP67, IP69(IP69K) |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating | high with crenellations plastic black IP66, IP67, IP69(IP69K) |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 vibration resistance | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h |
| design of the front ring material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance | high with crenellations plastic black IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 Sinusoidal half-wave 50g / 11 ms Category 1, Class B 10 500 Hz: 5g Category 1, Class B 3 600 1/h 10 000 000 |

| ambient temperature during storage | -40 +80 °C |
|---|---|
| environmental category during operation acc. to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %) |
| Installation/ mounting/ dimensions | |
| height | 29.5 mm |
| width | 29.5 mm |
| shape of the installation opening | round |
| mounting diameter | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm |
| mounting height | 18.1 mm |
| installation width | 29.5 mm |
| installation depth | 24.3 mm |
| Certificates/ approvals | |
| Further information | |

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-0DB40-0AA0-Z Y12

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1000-0DB40-0AA0-Z\ Y12}$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-0DB40-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-0DB40-0AA0-Z Y12&lang=en

last modified: 12/21/2020 🖸