

Coaxial Cable Connector 11_TNC-50-4-61/133_N

Description

Straight cable plug

Interface standards

IEC 60169-17_MIL-STD-348A/313_CECC 22200

Technical Data

Electrical Data

| | |
|--------------------------|--------|
| Impedance | 50 Ω |
| Interface frequency max. | 11 GHz |

Mechanical Data

| | |
|----------------|-------------|
| Centre contact | plugged |
| Outer contact | crimped |
| Weight | 0.017414 kg |

Environmental Data

| | |
|------------------------------------------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|-----------------|--------------------------------|-----------------------------------|
| Centre contact | Bronze | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Other body part | Brass | SUCOPLATE (R) Plating |
| Insulator | PTFE (Polytetrafluoroethylene) | |
| Coupling nut | Brass | SUCOPLATE (R) Plating |
| Gasket | VMQ (Silicone rubber) | |
| Crimp ferrule | Copper | SUCOPLATE (R) Plating |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00167330 |
| Assembly instruction | DOC-0000347599 |

Ordering Information

| | |
|----------------------|-----------------------|
| Bulk 100 pcs package | 11_TNC-50-4-61/133_NH |
|----------------------|-----------------------|

Additional Information

| | |
|-----------------|---------------|
| Suitable cables | SX_04172_B-60 |
|-----------------|---------------|