



Product: MEDIAFLEX DG FACEPLATE KITS ☑

MediaFlex 2-Gang Faceplate Kit

Product Description

MediaFlex Faceplate Kit, Double Gang. Available in several colors and port counts.

Technical Specifications

Product Overview

Suitable Applications:	Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800,3600, 2400 and 1200

Physical Characteristics (Overall)

Height:	4.62 m
Width:	5.31
Depth:	0.805
Front Connection:	Flush
Packaging:	Individually packaged in a plastic bag.
Weight:	0.233 kg

Connectors

Materials

Description	Material
Faceplate	Plastic - UL94V-0
Insert	Plastic - UL94V-0

Temperature Range

Installation Temperature Range:	-10 to 60°C
Storage Temperature Range:	-40 to 70°C
Operating Temperature Range:	-10 to 60°C

Mechanical Characteristics

Footprint/Type:	Mediaflex
Connector/Hardware Retention:	20 lbs

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	ACA, Bi-national Standard Listed

Related Part Numbers

Related Parts:	Compatible with 10GX, CAT6+ and CAT5E KeyConnect Modular Jacks and KeyConnect Multimedia Modules

Variants

Item #	Color	Port Count
AX102434	Almond	12 Port
AX102436	Almond	8 Port
AX102519	Almond	8 Port
AX102521	Almond	6 Port
AX102523	Almond	6 Port
AX104492	Black	12 Port
AX105770	Black	6 Port
AX105772	Black	8 Port
AX105774	Black	6 Port
AX105776	Black	8 Port
AX102435	Electric White	12 Port
AX102437	Electric White	8 Port
AX102520	Electric White	8 Port
AX102522	Electric White	6 Port
AX102524	Electric White	6 Port
AX104488	Gray	12 Port
AX105769	Gray	6 Port
AX105771	Gray	8 Port
AX105773	Gray	6 Port
AX105775	Gray	8 Port
AX105782	Ivory	8 Port
AX105783	Ivory	8 Port
AX105784	Ivory	12 Port
AX105785	Ivory	6 Port
AX105786	Ivory	8 Port

Product Notes

Included Parts:	Windows, paper, 6-32 screws, 2-port insert, blank, installation guide
Notes:	For proper installation refer to Installation Guide PX102063 included with the product or visit our web site at http://www.belden.com

History

Update and Revision:	Revision Number: 0.163 Revision Date: 03-04-2023

© 2023 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.