

Within Series Adaptor 32_MFBX-50-0-1/111_N

Description

Adaptor plug/plug
MFBX plug (male) / MFBX plug (male)

Slide - snap interface

Interface standard
Series MFBX - HUBER+SUHNER MFBX



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Number of matings 50
Weight 0.00076 kg

Environmental Data

Operating temperature -55 °C to 155 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Interface - MFBX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE / LCP	

Interface - MFBX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE / LCP	

Related Documents

Outline drawing DOU-00234712

Ordering Information

Single package 32_MFBX-50-0-1/111_NE
Bulk 100 pcs package 32_MFBX-50-0-1/111_NH-2