

**RS RJ45**  
**RS RJ45 2WAY****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

The RS RJ45 interface range is a simple and convenient alternative for connecting modems, routers, computers or other communication elements with existing components in electrical cabinets.

They can be used to adapt the shielded RJ45 8-pole connectors to screw connections, or for coupling 2 data lines. The modules can be attached to standard TS35 mounting rails.

**General ordering data**

Type	RS RJ45 2WAY
Order No.	<a href="#">8555440000</a>
Version	Interface, RS RJ45, 2 x RJ45 connector
GTIN (EAN)	4032248193882
Qty.	1 pc(s).

**Data sheet**

**RS RJ45  
RS RJ45 2WAY**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	46.8 mm	Width	45 mm
Height	44.2 mm	Net weight	60 g

**Temperatures**

Operating temperature	0...+55°C	Storage temperature	-40...+70 °C
-----------------------	-----------	---------------------	--------------

**Connection Data**

Connection on control side	2 x RJ45 connector	Contact material (control side)	Phosphor-bronze 6µ AU
Connection (field side)	2 x RJ45 plug-in connectors	Number of poles (field side)	8 P
Transmission rate	Cat 5 100 Mbits		

**Rating data**

Rated voltage	50 V	Rated current per connection	1 A
Total operating current	1.5 A		

**Insulation coordination (EN50178)**

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Pulse voltage test (1,2/50µs)	0.8 kV	Insulation test voltage	0.35 kVAC

**Classifications**

ETIM 3.0	EC001419	UNSPSC	30-21-18-01
eClass 5.1	27-24-22-04	eClass 6.2	27-24-22-04
eClass 7.1	27-24-22-04		

**Product information**

Descriptive text technical data	Connect shielding of data line to protective earth at one end
---------------------------------	---

**Approvals**

Approvals



ROHS	Conform
------	---------

**Data sheet**

**RS RJ45  
RS RJ45 2WAY**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

