



Product: MEDIAFLEX ANG EDGE DG FP KITS ☑

MediaFlex Angled Edge 2-Gang Faceplate Kit

Product Description

MediaFlex Angled Edge Faceplate Kit, Double Gang. Available in several colors.

Technical Specifications

Product Overview

Suitable Applications:	Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800,3600, 2400 and 1200

Physical Characteristics (Overall)

Height:	4.5 m
Width:	4.586
Depth:	1.14
Front Connection:	Angled
Packaging:	Individually packaged in a plastic bag.
Weight:	0.2 kg

Connectors

Materials

Description	Material	
Faceplate	High-impact Thermoplastic, flame-retardant UL94V-0, UV-resistant	
Insert	High-impact Thermoplastic, flame-retardant UL94V-0, UV-resistant	

Temperature Range

Installation Temperature Range:	-10 to 60°C
Storage Temperature Range:	-40 to 70°C
Operating Temperature Range:	-10 to 60°C

Mechanical Characteristics

Footprint/Type:	Mediaflex
Connector/Hardware Retention:	20 lbs

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2011/65/EU (RoHS 2):	Yes
MII Order #39 (China RoHS):	EUP 50

Related Part Numbers

Related Parts:	Compatible with 10GX, CAT6+ and CAT5E KeyConnect Modular Jacks and KeyConnect Multimedia Modules

Variants

Item #	Color	Port Count
AX106638	Almond	6 Port
AX106642	Almond	8 Port

AX106646	Almond	12 Port
AX106650	Almond	6 Port
AX106654	Almond	8 Port
AX106640	Black	6 Port
AX106644	Black	8 Port
AX106648	Black	12 Port
AX106652	Black	6 Port
AX106656	Black	8 Port
AX106639	Electric White	6 Port
AX106643	Electric White	8 Port
AX106647	Electric White	12 Port
AX106651	Electric White	6 Port
AX106655	Electric White	8 Port
AX106637	Gray	6 Port
AX106641	Gray	8 Port
AX106645	Gray	12 Port
AX106649	Gray	6 Port
AX106653	Gray	8 Port

Product Notes

Included Parts:	windows, papers, 6-32 screws, 2-port inserts, blanks, installation guide
Notes:	For proper installation refer to Installation Guide PX106224 included with the product or visit our web site at http://www.belden.com

History

Update and Revision:	Revision Number: 0.61 Revision Date: 03-04-2023

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.