



Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Application	Modular distribution application Multi-purpose
Product or Component Type	Chassis
Device short name	DLS
For enclosure nominal dimensions	-
Mounting Location	Front of enclosure
Range compatibility	Thalassa PLS
Device composition	1 chassis structure 1 front panel 2 35 mm DIN rail

Complementary

Material	Front panel self-extinguishing Chassis structure and rails galvanised steel
Color	Front panel Gray RAL 7032)
Fixing mode	By fixing element - on front with supports
Number of horizontal rows	2
Total number of 18 mm modules	24
Type of front plate	Cut-out plate
Number of cut-out	2 cut-outs

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480188466
Nbr. of units in pkg.	1
Package weight(Lbs)	27.09 oz (768.0 g)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.54 in (9 cm)
Package 1 width	10.24 in (26 cm)
Package 1 Length	10.24 in (26 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------