3SU1051-0AA50-0AA0-Z Y12

Data sheet



Illuminated pushbutton, 22 mm, round, metal, shiny, blue, pushbutton, flat, latching, Push-to-release mechanism, with laser labeling, lower case

| product designation design of the product product type designation product line Enclosure number of command points Actuator design of the actuating element principle of operation of the actuating element product extension optional elight source color of the actuating element practical fine actuating element practical fine actuating element product extension optional elight source pochate material of the actuating element practical fine actuating element product extension optional elight source pochate module product extension optional elight source poch contact module product extension optional elight source poch contact module poch contact module poch contact module plastic plastic plastic shape of the actuating element plastic shape of the actuating element cound puter diameter of the actuating element pround potent plastic plastic pround potent plastic plasti | |
|--|--|
| product type designation product line Enclosure number of command points Actuator design of the actuating element principle of operation of the actuating element Flat button Iatching Product extension optional Iight source Contact module Color of the actuating element Diue Imaterial of the actuating element Plat button Diagraphic product extension optional Iatching Yes Color of the actuating element Diue Diue Diue Diastic Shape of the actuating element Diastic Shape of the actuating element Customized labeling, text in lower case letters | |
| product line Enclosure number of command points Actuator design of the actuating element principle of operation of the actuating element product extension optional • light source Yes • contact module Yes color of the actuating element plastic material of the actuating element plastic shape of the actuating element round outer diameter of the actuating element 29.5 mm marking of the actuating element Customized labeling, text in lower case letters | |
| number of command points Actuator design of the actuating element | |
| number of command points Actuator design of the actuating element Flat button principle of operation of the actuating element latching product extension optional Ight source Yes contact module Yes color of the actuating element blue material of the actuating element plastic shape of the actuating element round outer diameter of the actuating element 29.5 mm marking of the actuating element Customized labeling, text in lower case letters | |
| Actuator design of the actuating element Flat button principle of operation of the actuating element latching product extension optional • light source Yes • contact module Yes color of the actuating element blue material of the actuating element plastic shape of the actuating element round outer diameter of the actuating element 29.5 mm marking of the actuating element Customized labeling, text in lower case letters | |
| design of the actuating element principle of operation of the actuating element product extension optional light source contact module color of the actuating element blue material of the actuating element plastic shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case letters | |
| principle of operation of the actuating element product extension optional • light source • contact module color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case letters | |
| product extension optional Ight source contact module color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element customized labeling, text in lower case letters | |
| ● light source ● contact module Color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case letters | |
| ● contact module Color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case letters | |
| color of the actuating element material of the actuating element shape of the actuating element outer diameter of the actuating element marking of the actuating element Customized labeling, text in lower case letters | |
| material of the actuating element plastic shape of the actuating element round outer diameter of the actuating element 29.5 mm marking of the actuating element Customized labeling, text in lower case letters | |
| shape of the actuating elementroundouter diameter of the actuating element29.5 mmmarking of the actuating elementCustomized labeling, text in lower case letters | |
| outer diameter of the actuating element 29.5 mm marking of the actuating element Customized labeling, text in lower case letters | |
| marking of the actuating element Customized labeling, text in lower case letters | |
| | |
| | |
| type of unlocking device push-to-unlatch mechanism | |
| Front ring | |
| product component front ring Yes | |
| design of the front ring Standard | |
| material of the front ring Metal, high gloss | |
| color of the front ring silver | |
| General technical data | |
| protection class IP IP66, IP67, IP69(IP69K) | |
| degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 | |
| shock resistance | |
| • acc. to IEC 60068-2-27 Sinusoidal half-wave 50g / 11 ms | |
| vibration resistance | |
| • acc. to IEC 60068-2-6 10 500 Hz: 5g | |
| operating frequency maximum 1 800 1/h | |
| mechanical service life (switching cycles) typical 500 000 | |
| reference code acc. to IEC 81346-2 | |
| Ambient conditions | |
| • ambient temperature during operation -25 +70 °C | |
| • ambient temperature during storage -40 +80 °C | |

| environmental category during operation acc. to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %) |
|---|---|
| Installation/ mounting/ dimensions | |
| height | 29.5 mm |
| width | 29.5 mm |
| shape of the installation opening | round |
| mounting diameter | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm |
| mounting height | 11 mm |
| installation width | 29.5 mm |
| installation depth | 24.3 mm |
| Certificates/ approvals | |
| Further information | |

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1051-0AA50-0AA0-Z Y12

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1051-0AA50-0AA0-Z Y12

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1051-0AA50-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1051-0AA50-0AA0-Z Y12&lang=en

| ast modified: | 12/21/2020 | 3 |
|---------------|------------|---|
| | | |