

Product data sheet

Specifications



9007, limit switch 600 V 10amp c special +opti

9007C54CS17

Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Type of operator	spring return lever arm (to be ordered separately maintained)
Switch actuation	CW and CCW
Cable entry	NPT conduit entry, cable outer diameter: 12.70 mm
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	0.34 N.m
Tripping angle	45 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, A600 10 A, Q600
[Ui] rated insulation voltage	600 V
Product certifications	CE CSA UL listed
Provided equipment	Receptacle

Environment

Ambient air temperature for operation	-29...85 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.806 cm
Package 1 Width	10.16 cm
Package 1 Length	65.548 cm
Package 1 Weight	566.991 g

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Recommended replacement(s)