

Interlock bolt PRO for locking the inclination adjustment Further information, quantity and content: See technical specifications



Figure similar

General information	
Product type designation	PRO interlock bolts:
Installation type/mounting	
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Degree and class of protection	
IP (all-round)	none
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C
• max.	80 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	90 %
Mechanics/material	
Interlock design	M8 screw fastening
Enclosure material (front)	
• Plastic	Yes; mushroom knob, thermoplast, black gray
• Stainless steel	Yes; pin, hardened
Torques/forces	
• Tightening torque, min.	0.18 N·m; If there is not enough torque, the degree of protection on the front may not be guaranteed
• Tightening torque, max.	0.2 N·m
• Tightening torque, recommended	0.2 N·m; Higher torques may damage the product
Dimensions	
Length	40.5 mm; total length
Diameter	8 mm
Weights	
Weight (without packaging)	5 g; Per unit
Weight (with packaging)	6 g; Delivery unit
Scope of supply	
Delivery quantity in pieces	1; Units per set
Other	
Merchandise	Yes; 03093-201004
Manufacturer name	Berner + Straller GmbH
Manufacturer's address	Wörnitzstr. 117, 90449 Nuremberg, Deutschland

contacting the manufacturer	Email: <a href="mailto:nuernberg@berner-straller.de">nuernberg@berner-straller.de</a>
Target devices	for locking inclination adjustments, e.g. suitable for keyboards or shelves
Usable in the following products	
<ul style="list-style-type: none"><li>• Product 1</li><li>• Product 2</li><li>• Product 3</li><li>• Product 4</li><li>• Product 5</li></ul>	<a href="#">6AV7674-0NE00-0AA0</a> <a href="#">6AV7674-1NE00-0AA0</a> <a href="#">6AV7674-0NE01-0AA0</a> <a href="#">6AV7674-1NE01-0AA0</a> <a href="#">6AV7674-1NF01-0AA0</a>
<b>last modified:</b>	8/24/2021 