

**WK S 0,6x3,5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Interchangeable bits for torque screwdriver**

Drive output acc. to DIN 5264, ISO 2380/1

**General ordering data**

Type	WK S 0,6x3,5
Order No.	<a href="#">9918540000</a>
Version	Screwdriver insert, Blade width (B): 3.5 mm, 175 mm, Blade thickness (A): 0.6 mm
GTIN (EAN)	4032248388905
Qty.	1 pc(s).

## WK S 0,6x3,5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

## Dimensions and weights

Width	175 mm	Width (inches)	6.89 inch
Height	4 mm	Height (inches)	0.157 inch
Depth	4 mm	Depth (inches)	0.157 inch
Weight	26 g	Net weight	22 g

## Environmental Product Compliance

REACH SVHC Lead 7439-92-1

## Screwing tools

Blade length	175 mm	Blade thickness (A)	0.6 mm
Blade width (B)	3.5 mm	Form	Slotted

## Classifications

ETIM 3.0	EC001395	ETIM 4.0	EC001395
ETIM 5.0	EC001395	ETIM 6.0	EC002116
UNSPSC	27-11-28-14	eClass 5.1	21-04-04-02
eClass 6.2	21-04-92-21	eClass 7.1	21-04-04-90
eClass 8.1	21-04-04-90	eClass 9.0	21-04-04-00
eClass 9.1	21-04-04-90		

## Approvals

Approvals



## Downloads

Brochure/Catalogue [CAT 3 HDC 17/18 EN](#)  
[CAT 6 TOOLS 15/16 EN](#)  
[CAT 5 ENCL 17/18 EN](#)