

box terminal w. control wire voltage tap-off 4 units accessory for: 3VA6 150/250



Model	
product brand name	SETRON
product designation	accessories
Accessories	Box terminal
General technical data	
designation / of the terminal	TS1.4
Connections according IEC	
connectable conductor cross-section	
<ul style="list-style-type: none"> for copper cable / stranded / minimum for copper cable / stranded / maximum 	25 mm ² 185 mm ²
stripped length	20 mm
tightening torque / when using copper cables	
<ul style="list-style-type: none"> stranded finely stranded 	25 - 35 mm ² : 6 Nm 50 - 185 mm ² : 12 Nm 35 mm ² : 6 Nm 50 - 150 mm ² : 12 Nm
Connections according UL	
stripped length	0.8 in
connectable conductor cross-section	
<ul style="list-style-type: none"> for copper cable / stranded / minimum for copper cable / stranded / maximum for copper cable / finely stranded / minimum for copper cable / finely stranded / maximum 	4 AWG 350 kcmil 4 AWG 350 kcmil
tightening torque / when using copper cables	
<ul style="list-style-type: none"> stranded finely stranded 	4 - 1 AWG: 70 lb-in 1/0 - 350 kcmil: 140 lb-in 4 - 1 AWG: 70 lb-in 1/0 - 350 kcmil: 140 lb-in
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9244-0JH12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9244-0JH12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9244-0JH12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

7/5/2022

