



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .01 (.254mm)	B IN (mm) +/- .01 (.254mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .01 (.254mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	H IN (mm) +/- .005 (.127mm)	ANSI/UL 94 MH FLAMABILITY RATING	SCREW SIZE
AP (R,L)-SM0-9	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.132 (3.352mm)	.270 (6.858mm)	.100 (2.540mm)	94 V-2	#4 SCREW
AP (R,L)-SM0-0	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.132 (3.352mm)	.270 (6.858mm)	.100 (2.540mm)	94 V-2	#4 SCREW
AP (R,L)-SM0-30	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.132 (3.352mm)	.270 (6.858mm)	.100 (2.540mm)	94 V-2	#4 SCREW
AP (R,L)-SM1-9	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.160 (4.064mm)	.280 (7.112mm)	.100 (2.540mm)	94 V-2	#6 SCREW
AP (R,L)-SM1-0	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.160 (4.064mm)	.280 (7.112mm)	.100 (2.540mm)	94 V-2	#6 SCREW
AP (R,L)-SM1-30	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.160 (4.064mm)	.280 (7.112mm)	.100 (2.540mm)	94 V-2	#6 SCREW
AP (R,L)-SM2-9	.90 (22.860mm)	.63 (16.002mm)	.350 (8.890mm)	.38 (9.652mm)	.125 (3.175mm)	.270 (6.858mm)	.490 (12.446mm)	.130 (3.302mm)	94 V-2	1/4 SCREW
AP (R,L)-SM2-0	.90 (22.860mm)	.63 (16.002mm)	.350 (8.890mm)	.38 (9.652mm)	.125 (3.175mm)	.270 (6.858mm)	.490 (12.446mm)	.130 (3.302mm)	94 V-2	1/4 SCREW
AP (R,L)-SM2-30	.90 (22.860mm)	.63 (16.002mm)	.350 (8.890mm)	.38 (9.652mm)	.125 (3.175mm)	.270 (6.858mm)	.490 (12.446mm)	.130 (3.302mm)	94 V-2	1/4 SCREW
AP (R,L)-SM3-9	.90 (22.860mm)	.63 (16.002mm)	.350 (8.890mm)	.38 (9.652mm)	.125 (3.175mm)	.210 (5.334mm)	.430 (10.922mm)	.130 (3.302mm)	94 V-2	#10 SCREW
AP (R,L)-SM3-0	.90 (22.860mm)	.63 (16.002mm)	.350 (8.890mm)	.38 (9.652mm)	.125 (3.175mm)	.210 (5.334mm)	.430 (10.922mm)	.130 (3.302mm)	94 V-2	#10 SCREW
AP (R,L)-SM3-30	.90 (22.860mm)	.63 (16.002mm)	.350 (8.890mm)	.38 (9.652mm)	.125 (3.175mm)	.210 (5.334mm)	.430 (10.922mm)	.130 (3.302mm)	94 V-2	#10 SCREW
AP (R,L)-SM8-9	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.188 (4.775mm)	.325 (8.255mm)	.100 (2.540mm)	94 V-2	#8 SCREW
AP (R,L)-SM8-0	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.188 (4.775mm)	.325 (8.255mm)	.100 (2.540mm)	94 V-2	#8 SCREW
AP (R,L)-SM8-30	.60 (15.240mm)	.38 (9.652mm)	.200 (5.080mm)	.27 (6.858mm)	.065 (1.651mm)	.188 (4.775mm)	.325 (8.255mm)	.100 (2.540mm)	94 V-2	#8 SCREW



ADVANCED CABLE TIES – SCREW MOUNTS

COLOR DESIGNATIONS:

0 = UV BLACK 9 = NATURAL 30 = HEAT STABILIZED

MATERIAL:

NYLON 6/6 POLYAMIDE

B	4/29/17	JA	KT	KT	NEW LOGO ADDED	SHEET 1 OF 1	REV.: B	DRAWING NO.: SM-B	
A	4/16/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	4/29/17	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.55.2