

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

2. MODIFICATIONS: THREADED ADAPTER; REDUCED DIA. WIRE SEAL

- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE:

IP68(IM OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION);

IP69K(MATED CONDITION)


3.5 MATING CYCLE DURABILITY: 100 CYCLES


- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP06-24-19S* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6 CONTACT SIZE AND WIRE RANGE:


CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
12	3.43 mm (.135 in)	4.32 mm (.170 in)	10-14 AWG (6.0-2.0mm²)	25 AMPS
16	2.54 mm (.100in)	3.40 mm (.134 in)	14-20 AWG (2.0-0.5mm²)	13 AMPS

7.RECEPTACLE IS SUPPLIED WITH DUST CAP.









THREADED ADAPTER - GREEN

Ø43.08±0.12	
ENDED PANEL FING HOLE	

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM

				_	
	AHDP04-24-19PN-WTA			1 5	
ANTITY	PART NUMBER	DESCRIPTION	ITEM	-	
MATERIALS LIST					

		MAT	ERI	4
UNLESS OTHERWISE SPECIFIED	SIGNATURES		DATE	
1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64.	DRAWN:	LYNCH	03NOV21	
1 PL DEC ±0.30 Fractions ±1/64 2 PL DEC ±0.15 Angles ±1° 3 PL DEC ±0.06	CHECKED:	SULLEN	03NOV21	ĺ
3) Note reference = X	ENGINEER:			
MATERIAL SPECIFICATIONS:	APPROVAL:	TOMMY	05NOV21	┝
WEIGHT:48.05G	CUSTOMER:		•	
PROCESS SPECIFICATIONS:	INFORMATION SPECIFICATION SHOWN HERE THE AMPHENIOF REPRODU	IS SUPPLIED FOR ONLY, DESIGN FOR AND PERFORM ON ARE THE PRODUCTION ARE IMPLIBATE SUBJECT TO	EATURES, MANCE DATA OPERTY OF N. NO RIGHTS ED. ALL	SIZ
NEXT ASS'Y:		ING VARIATIONS		SCA

Amphenol

TITLE: RECEPTACLE,24-19 POS, PIN CONT.,STANDARD DIA. SEAL, AHDP

AHDP04-24-19PN-WTA REV: A4 SH:

44724 Morley Drive Clinton Township, MI 48036

RECEPTACLE,24-19 POS, PIN CONTACT STANDARD DIA. SEAL, AHDP SERIES

CALE: NONE SHEET 1 OF 1

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins							
Part Number	Description	Size	AWG	Туре			
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined			
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined			
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined			
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined			
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined			
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined			
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined			
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined			
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined			
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined			
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined			
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined			

Tooling - Machined Contacts						
Part	Part Number	Description				
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)				
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)				

Contact Removal Tools								
Part	Part Number Description							
	ATRT-100	Used for removal of contacts for A Series™ products						
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16						

	Sealing Plugs						
Part	Part Number	Description					
	A114017	Sealing Plug, Size 16, White					
	A114017-SR	Sealing Plug, Size 16, SR01 Series, Black					
	AT13-217-1605	Locking Sealing Plug, Size 16, Grey					
	AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red					

Stamped & Formed Contacts, Sockets & Pins							
Part Number	Description	Size	AWG	Туре			
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed			
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed			
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed			
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed			
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed			
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed			
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed			
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed			
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed			
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed			
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed			
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed			
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed			
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed			
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed			
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed			

Tooling - Stamped & Formed Contacts						
Part	Part Number	Description				
e de la composição de l	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)				
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)				
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)				
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)				
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)				
0	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)				
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)				

DuraMate™ AHDP - Contact Size 12 Options

Machined Contacts, Sockets & Pins							
Part Number	Part Number Description						
AT60-204-12141-10	Male Contact - Pin, Nickel-plated	12	10-12	Machined			
AT62-203-12141-10	Female Contact - Socket, Nickel-plated	12	10-12	Machined			
AT60-220-1231	Male Contact - Pin, Gold-plated	12	12-14	Machined			
AT62-210-1231	Female Contact - Socket, Gold-plated	12	12-14	Machined			
AT60-204-12141	Male Contact - Pin, Nickel-plated	12	12-14	Machined			
AT62-203-12141	Female Contact - Socket, Nickel-plated	12	12-14	Machined			

• Smaller AWG f	DiagnosticGrade™ Machined Contacts, Sockets & Pins • Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective						
Part Number	Size	AWG	Туре				
65-54749	Male Contact - DiagnosticGrade™, Pin, Gold-plated	12	20	Machined			
AT62-210-1231-1820	Female Contact - DiagnosticGrade™, Socket, Gold-plated	12	20	Machined			

Tooling - Machined Contacts				
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
33	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

Contact Removal Tools				
Part	Part Number	Description		
	AT11-337-1205	Contact Removal Tool, Plastic, Size 12		
	A114017	Sealing Plug, Size 12, White		

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description		AWG	Туре		
AT60-12-0244	Male Contact - Pin, Gold-plated	12	10-12	Stamped & Formed		
AT62-12-0244	Female Contact - Socket, Gold-plated	12	10-12	Stamped & Formed		
AT60-12-0222	Male Contact - Pin, Nickel-plated	12	10-12	Stamped & Formed		
AT62-12-0222	Female Contact - Socket, Nickel-plated	12	10-12	Stamped & Formed		
AT60-12-0144	Male Contact - Pin, Gold-plated	12	12-14	Stamped & Formed		
AT62-12-0144	Female Contact - Socket, Gold-plated	12	12-14	Stamped & Formed		
AT60-12-0166	Male Contact - Pin, Nickel-plated	12	12-14	Stamped & Formed		
AT62-12-0166	Female Contact - Socket, Nickel-plated	12	12-14	Stamped & Formed		

Tooling - Stamped & Formed Contacts				
Part	Part Number	Description		
	MFX-3973	Crimp Die - Size 12 (S&F contacts only)		
	MFX-3985	Crimp Die - Size 12 (S&F contacts only) 10-12AWG -02XX Series		
	ATT-12-00	Hand Crimp Tool - Size 12, 12AWG (S&F contacts only)		
	АП-12-01	Hand Crimp Tool - Size 12, 10AWG (S&F contacts only)		