





NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

2. MODIFICATIONS: BACKSHELL RING ADAPTER (BRA);

REDUCED DIA. WIRE SEAL;

- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE:

IP68(IM OF WATER FOR A PERIOD OF 24 HOURS, MATED

CONDITION);

IP69K(MATED CONDITION)

- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP02-24-31P* & AHDP04-24-31P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
16	1.35 mm (.053 in)	2.62 mm (.103 in)	14-20 AWG (2.0-0.5mm²)	13 AMPS



BACKSHELL RING ADAPTER -BLUE

	AHDP06-24-31SR-BRA		-BRA	REF:HDP26-24-31SE-L017					
QUANTITY	PART NUMBER		R	DESCRIPTION					
			MAT	FERI	٩LS	3 LI	ST		
UNLESS OTHERWISE SPECIFIED		SIGNATURES		B DATE	Amphonol				
1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference = X MATERIAL SPECIFICATIONS: WEIGHT: 61g		DRAWN: IAN.XIAO		01/MAR/22	Amphenol Sine Systems - www.amphenol-sine.com				
		CHECKED: SULLEN.ZHANG		02/MAR/22					
		ENGINEER:				44724 Morley Drive			
		APPROVAL:	TOMMY.XIE	03/MAR/22		Clinton Township, MI 48036			
		CUSTOMER:		31POS,PLUG,SOCKET,24SZ, RD SEAL,BRA,DURAMATE AHDP					
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL							
PROCESS SPECIFICATIONS:				SIZE	C-	AHDP06-24-31SR-BRA	A'		
NEXT ASS'Y:				SCALE: N	ONE	DURAMATE SHEET 1	OF 1		

유