

1	2	3	4	5	6	7	A																																					
<p>Electrical Character</p> <table border="1"> <thead> <tr> <th rowspan="2">Part Nuber</th> <th rowspan="2">Contacts</th> <th colspan="2">Rated Voltage</th> <th rowspan="2">Rated Current</th> <th rowspan="2">Contact Resistance</th> <th rowspan="2">Cable OD (mm)</th> </tr> <tr> <th>A/C</th> <th>D/C</th> </tr> </thead> <tbody> <tr> <td>A-M12-03-MAPA-GEB1a</td> <td></td> <td>250V</td> <td>250V</td> <td>4A</td> <td>≤10mΩ</td> <td>6~8</td> </tr> <tr> <td>A-M12-04-MAPA-GEB1a</td> <td></td> <td>250V</td> <td>250V</td> <td>4A</td> <td>≤10mΩ</td> <td>6~8</td> </tr> <tr> <td>A-M12-05-MAPA-GEB1a</td> <td></td> <td>60V</td> <td>60V</td> <td>4A</td> <td>≤10mΩ</td> <td>6~8</td> </tr> <tr> <td>A-M12-08-MAPA-GEB1a</td> <td></td> <td>30V</td> <td>30V</td> <td>2A</td> <td>≤10mΩ</td> <td>6~8</td> </tr> </tbody> </table>								Part Nuber	Contacts	Rated Voltage		Rated Current	Contact Resistance	Cable OD (mm)	A/C	D/C	A-M12-03-MAPA-GEB1a		250V	250V	4A	≤10mΩ	6~8	A-M12-04-MAPA-GEB1a		250V	250V	4A	≤10mΩ	6~8	A-M12-05-MAPA-GEB1a		60V	60V	4A	≤10mΩ	6~8	A-M12-08-MAPA-GEB1a		30V	30V	2A	≤10mΩ	6~8
Part Nuber	Contacts	Rated Voltage		Rated Current	Contact Resistance	Cable OD (mm)																																						
		A/C	D/C																																									
A-M12-03-MAPA-GEB1a		250V	250V	4A	≤10mΩ	6~8																																						
A-M12-04-MAPA-GEB1a		250V	250V	4A	≤10mΩ	6~8																																						
A-M12-05-MAPA-GEB1a		60V	60V	4A	≤10mΩ	6~8																																						
A-M12-08-MAPA-GEB1a		30V	30V	2A	≤10mΩ	6~8																																						
<p>Notes:</p> <ol style="list-style-type: none"> <li>1. Waterproof connector rating is IP67/IP68</li> <li>2. Contact PIN: Brass with 1u" Gold plating</li> <li>3. Coupling nut/screw: Brass with nickel plating</li> <li>4. Insulation plastic: PA66+GF Black, UL94V-0</li> <li>5. Insulation Resistance: &gt;100MΩ</li> <li>6. Mating Cycle: 100 times Min, 500 times Max.</li> <li>7. Operating temperature: -25°C ~ +85°C</li> <li>① 8. Unshielded</li> </ol>																																												
<p>RoHS compliant</p> <p>Unit: mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>.X</td> <td>±0.5</td> </tr> <tr> <td>.XX</td> <td>±0.20</td> </tr> <tr> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>X. °</td> <td>±2.0°</td> </tr> <tr> <td>.X°</td> <td>±1.0°</td> </tr> <tr> <td>Angle</td> <td>TOL</td> </tr> </tbody> </table>								Scale	Free TOLERANCE	.X	±0.5	.XX	±0.20	DIM	TOL	X. °	±2.0°	.X°	±1.0°	Angle	TOL																							
Scale	Free TOLERANCE																																											
.X	±0.5																																											
.XX	±0.20																																											
DIM	TOL																																											
X. °	±2.0°																																											
.X°	±1.0°																																											
Angle	TOL																																											
<table border="1"> <thead> <tr> <th>Scale</th> <th>Free TOLERANCE</th> <th>Free</th> </tr> </thead> <tbody> <tr> <td>.X</td> <td>±0.5</td> <td></td> </tr> <tr> <td>.XX</td> <td>±0.20</td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> </tr> <tr> <td>X. °</td> <td>±2.0°</td> <td></td> </tr> <tr> <td>.X°</td> <td>±1.0°</td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td></td> </tr> </tbody> </table>								Scale	Free TOLERANCE	Free	.X	±0.5		.XX	±0.20		DIM	TOL		X. °	±2.0°		.X°	±1.0°		Angle	TOL																	
Scale	Free TOLERANCE	Free																																										
.X	±0.5																																											
.XX	±0.20																																											
DIM	TOL																																											
X. °	±2.0°																																											
.X°	±1.0°																																											
Angle	TOL																																											
<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> </tr> </thead> <tbody> <tr> <td>①</td> <td>Update the notes</td> <td>26.04.2019</td> <td>Segal</td> </tr> <tr> <td>②</td> <td>Remove "resistance many oils and chemical" from notes</td> <td>06.09.2019</td> <td>Amy</td> </tr> <tr> <td>③</td> <td>Drawn</td> <td>29.06.2018</td> <td>Segal</td> </tr> </tbody> </table>								Id.	Modification	Date	Name	①	Update the notes	26.04.2019	Segal	②	Remove "resistance many oils and chemical" from notes	06.09.2019	Amy	③	Drawn	29.06.2018	Segal																					
Id.	Modification	Date	Name																																									
①	Update the notes	26.04.2019	Segal																																									
②	Remove "resistance many oils and chemical" from notes	06.09.2019	Amy																																									
③	Drawn	29.06.2018	Segal																																									
<table border="1"> <thead> <tr> <th>Date</th> <th>Name</th> <th>Customer-No.</th> <th>Drawing-No.</th> <th>Replace</th> <th>Sheet</th> </tr> </thead> <tbody> <tr> <td>29.06.2018</td> <td>Segal</td> <td>ASSMANN WSW-No.</td> <td>A-M12-xx-MAPA-GEB1a</td> <td>ASS 8023 CO</td> <td>rev02</td> </tr> <tr> <td>06.09.2019</td> <td>Amy</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>								Date	Name	Customer-No.	Drawing-No.	Replace	Sheet	29.06.2018	Segal	ASSMANN WSW-No.	A-M12-xx-MAPA-GEB1a	ASS 8023 CO	rev02	06.09.2019	Amy																							
Date	Name	Customer-No.	Drawing-No.	Replace	Sheet																																							
29.06.2018	Segal	ASSMANN WSW-No.	A-M12-xx-MAPA-GEB1a	ASS 8023 CO	rev02																																							
06.09.2019	Amy																																											
<p><b>ASSMANN</b> components</p>																																												
<p>SV4471</p>																																												