

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-2S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL		TYPICAL
SIZE	O.D.		WIRE RANGE
16	2.24 mm	3.68 mm	14 - 20 AWG
	(.088 in)	(.145 in)	(2.0-0.5mm²)




PART NUMBER CHART		
COLOR	PART NUMBER	
GREY	AT04-2P	
BLACK	AT04-2P-BLK	
BLUE	AT04-2P-BLU	
BROWN	AT04-2P-BRN	
GREEN	AT04-2P-GRN	
RED	AT04-2P-RED	
WHITE	AT04-2P-WHT	
YELLOW	AT04-2P-YEL	
ORANGE	AT04-2P-ORG	

		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
А3	-	RELEASE NEW DWG FORMAT	26DEC13	JARRY	
A4	C0540S	UPDATE DIMENSIONS	22JUN16	JONY	TOMMY
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY

RECEPTACLE, 2 PIN, AT SERIES

AT04-2P-XXX

REV: **A5** SH: 1



	SEE PART N	IMBER C	ΉΔRT		REF: DT	114.2P. DT	04-2P-F004		
								-	
	PARIN	IUMBER			DE	SCRIP	HON		ITT
QUANTITY		1	MAT	ERI	ALS LI	ST			
	WISE SPECIFIED	SIGN	IATURES	DATE			l		1
All dimensions a Tolerances are a PL DEC ±0.30		DRAWN:	LOUIE	23NOV20		ΛΠ	phe	s no	
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	24NOV20	Sin	e System	s - www.amph	enol-sine.com	
3) Note reference	- 🛦	ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	25NOV20		Cilliton	rownship, ivii 4	0030	
		CUSTOMER:			R	ECEPT	ACLE. 2 PI	IN. AT SER	IES.
			G IS SUPPLIED F				- ,	, -	-,
PROCESS SPECIFICA	TIONS:	SPECIFICATIO SHOWN HERE THE AMPHENO OF REPRODU	ONS AND PERFORM ON ARE THE PROPERTY OF CORPORATION OF THE PROPERTY OF THE PROP	RMANCE DATA OPERTY OF IN. NO RIGHTS IED. ALL	B C-	DWG NO:	AT04-2	P-XXX	A:
NEXT ASS'Y:			RING VARIATIONS		SCALE: NONE			SHEET 1	or 1

ADDITIONAL COLORS SHOWN IN PART NUMBER

CHART ARE AVAILABLE VIA SPECIAL ORDER.

A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined	

	Tooling - Machined Contacts			
Part Number	Description			
AUTK-20	Hand Crimp Tool, Size 20			
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20			
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20			
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20			

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)			
Part Number	Description		
ATRT-100	Contact and Wedgelock Extraction Tool		
AT11-310-1605	Contact Removal Tool, Plastic, Size 16		

Sealing Plugs (For both Machined or Stamped & Formed Contacts)			
Part Number	Description		
A114017	Sealing Plug, Size 16, White		
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black		
AT13-217-1605	Locking Sealing Plug, Size 16, Grey		
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red		

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

Tooling - Stamped & Formed Contacts		
MFX-3950	Crimp Die - Size 16, 18-20AWG	
MFX-3953	Crimp Die - Size 16, 16-18AWG	
MFX-3975	Crimp Die - Size 16, 14-16AWG	
MFX-3990	Crimp Die - Size 16, 20-22AWG	
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG	
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG	
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG	