


		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A3	-	RELEASE NEW DWG FORMAT	02JAN14	JARRY	
A4	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY

**REQUIRES CONTACT** RETENTION WEDGE AW2P



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: END CAP;

REDUCED DIA. WIRE SEAL


- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE:


IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-2S\* PLUG (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	1.35 mm (.053 in)		14 - 20 AWG (2.0-0.5mm <sup>2</sup> )





PART NUMBER CHART			
COLOR	PART NUMBER		
GREY	AT04-2P-MM01		
BLACK	AT04-2P-MM01BLK		
BLUE	AT04-2P-MM01BLU		
BROWN	AT04-2P-MM01BRN		
GREEN	AT04-2P-MM01GRN		
RED	AT04-2P-MM01RED		
WHITE	AT04-2P-MM01WHT		
YELLOW	AT04-2P-MM01YEL		
ORANGE	AT04-2P-MM01ORG		



ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	JMBER C	HART			REF: DT	04-2P-CE01 DT04-2P-CE	.03
	PART N	IUMBER				DE	SCRIPTION	
QUANTITY			MAT	ERI	ALS	} LI	ST	
	WISE SPECIFIED	SIGN	ATURES	DATE			mank	_
1) All dimensions a 2) Tolerances are a 1 PL DEC ±0.30		DRAWN:	LOUIE	23NOV20	1	~	mph	1
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	25NOV20		Sin	ie Systems - www.a	amp
3) Note reference	- <u>x</u>	ENGINEER:			44724 Morley Drive			
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20	<u> </u>	Clinton Township, M		
		CUSTOMER:			1		EPTACLE, 2 F	
		G IS SUPPLIED I		RED	UCEL	DIAMETER V	VIF	
PROCESS SPECIFICATIONS:		SPECIFICATIO SHOWN HERE THE AMPHENO OF REPRODUC	NS AND PERFO ON ARE THE PE	RMANCE DATA ROPERTY OF ON. NO RIGHTS LIED. ALL	B C- AT04-2P-N			<u>-</u> -N
			ING VARIATION		SCALE: N	IONE		

CRIPTION ITEM mphenol

RECEP., 2 PIN,AT SERIES,REDUCED DIA. WIRE SEAL,END CAP

DWG NO:

AT04-2P-EC01XXX

REV:

≴

왚

44724 Morley Drive Clinton Township, MI 48036

PTACLE, 2 PIN, AT SERIES, DIAMETER WIRE SEAL, END CAP

B	C-	AT04-2P-MM	01X	XX		A4
ALE: N	ONE		SHEET	1	OF	1

## A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins			
Part Number	Description	Size	AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined

Tooling - Machined Contacts		
Part Number	Description	
AUTK-20	Hand Crimp Tool, Size 20	
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20	
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20	
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20	

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)		
Part Number	Description	
ATRT-100	Contact and Wedgelock Extraction Tool	
AT11-310-1605	Contact Removal Tool, Plastic, Size 16	

	Sealing Plugs (For both Machined or Stamped & Formed Contacts)		
Part Number	Description		
A114017	Sealing Plug, Size 16, White		
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black		
AT13-217-1605	Locking Sealing Plug, Size 16, Grey		
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red		

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

	Tooling - Stamped & Formed Contacts		
MFX-3950	Crimp Die - Size 16, 18-20AWG		
MFX-3953	Crimp Die - Size 16, 16-18AWG		
MFX-3975	Crimp Die - Size 16, 14-16AWG		
MFX-3990	Crimp Die - Size 16, 20-22AWG		
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG		
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG		
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG		