


REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR	
A3	-	RELEASE NEW DWG FORMAT	02JAN14	JARRY		
A4	C0540S	UPDATE DIMENSIONS	05AUG16	JONY	TOMMY	
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY	


RECEPTACLE, 4 PIN,AT SERIES, END CAF

AT04-4P-EC01XXX

REV: A5

ΞΞ





NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: END CAP
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE: IP68(1M OF WATER FOR A PERIOD


IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION)

- IP69K(MATED CONDITION)
- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-4S\* PLUG (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6	6 CONTACT SIZE AND REAR SEAL WIRE RANGE:					
	CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE		
	16	2.24 mm (.088 in)	3.68 mm (.145 in)	14 - 20 AWG		



GREEN AT04-4P-EC01GRN RED AT04-4P-EC01RED WHITE AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL				
GREY AT04-4P-EC01 BLACK AT04-4P-EC01BLK BLUE AT04-4P-EC01BRN GREEN AT04-4P-EC01GRN RED AT04-4P-EC01RED WHITE AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL	PART NUMBER CHART			
BLACK AT04-4P-EC01BLK BLUE AT04-4P-EC01BLU BROWN AT04-4P-EC01BRN GREEN AT04-4P-EC01GRN RED AT04-4P-EC01RED WHITE AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL	COLOR	PART NUMBER		
BLUE AT04-4P-EC01BLU BROWN AT04-4P-EC01BRN GREEN AT04-4P-EC01GRN RED AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL	GREY	AT04-4P-EC01		
BROWN AT04-4P-EC01BRN GREEN AT04-4P-EC01GRN RED AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL	BLACK	AT04-4P-EC01BLK		
GREEN AT04-4P-EC01GRN RED AT04-4P-EC01RED WHITE AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL	BLUE	AT04-4P-EC01BLU		
RED AT04-4P-EC01RED WHITE AT04-4P-EC01WHI YELLOW AT04-4P-EC01YEL	BROWN	AT04-4P-EC01BRN		
WHITE AT04-4P-EC01WHT YELLOW AT04-4P-EC01YEL	GREEN	AT04-4P-EC01GRN		
YELLOW AT04-4P-EC01YEL	RED	AT04-4P-EC01RED		
	WHITE	AT04-4P-EC01WHT		
004110E 4T04 4D E0040D6	YELLOW	AT04-4P-EC01YEL		
ORANGE   ATO4-4P-EC01ORG	ORANGE	AT04-4P-EC01ORG		



STANDARD MOLDED COLOR IS GREY.
ADDITIONAL COLORS SHOWN IN PART NUMBER
CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	UMBER C	HART		REF: DT04-4P-E003, DT04-4P-EP04, DT04-4P-E005  DESCRIPTION		
	PART N	NUMBER					
QUANTITY			MAT	ERI	ALS LIST		
	WISE SPECIFIED	SIGN	ATURES	DATE	Λ		
All dimensions a     Tolerances are a     PL DEC ±0.30	s follows:	DRAWN:	LOUIE	23NOV20	Amphenol		
2 PL DEC ±0.15 3 PL DEC ±0.08	Fractions ±1/64 Angles ±1°	CHECKED:	ORION	25NOV20	Sine Systems - www.amphenol-sine.com		
3) Note reference	- 🗴	ENGINEER:		44724 Morley Drive			
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20	Clinton Township, MI 48036		
		CUSTOMER:			RECEPTACLE, 4 PIN.AT SERIES, END C	AP	
PROCESS SPECIFICATIONS:		INFORMATION SPECIFICATION SHOWN HERE	ON ARE THE PR	FEATURES, RMANCE DATA	SIZE TYPE DWG NO:  AT04-4P-EC01XXX	REVISION	
NEXT ASS'Y:		OF REPRODU	CTION ARE IMPI ARE SUBJECT T ING VARIATION	LIED. ALL O NORMAL	SCALE: NONE SHEET 1 OF	A3 1	

## A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре		
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined		
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined		
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined		
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined		
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined		
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined		
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined		
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined		
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined		
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined		
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined		
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined		

	Tooling - Machined Contacts				
Part Number	Description				
AUTK-20	Hand Crimp Tool, Size 20				
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20				
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20				
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20				

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)				
Part Number	Description			
ATRT-100	Contact and Wedgelock Extraction Tool			
AT11-310-1605	Contact Removal Tool, Plastic, Size 16			

Sealing Plugs (For both Machined or Stamped & Formed Contacts)				
Part Number	Description			
A114017	Sealing Plug, Size 16, White			
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black			
AT13-217-1605	Locking Sealing Plug, Size 16, Grey			
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red			

Stamped & Formed Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed	
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed	
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed	
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed	
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed	
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed	
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed	
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed	
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed	
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed	
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed	
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed	
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed	
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed	
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed	
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed	

	Tooling - Stamped & Formed Contacts		
MFX-3950	Crimp Die - Size 16, 18-20AWG		
MFX-3953	Crimp Die - Size 16, 16-18AWG		
MFX-3975	Crimp Die - Size 16, 14-16AWG		
MFX-3990	Crimp Die - Size 16, 20-22AWG		
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG		
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG		
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG		