



REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
A3	-	RELEASE NEW DWG FORMAT	12DEC13	DRP	
A4	C0540S	UPDATE DIMENSIONS	23JUN16	JONY	TOMMY
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY


PLUG, 2 SOCKET, AT SERIES, REDUCED DIA. WIRE SEAL

AT06-2S-RD01XXX

3







NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT04-2P* RECEPTACLE (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

<u>/6</u> \	6 CONTACT SIZE AND REAR SEAL WIRE RANGE:					
	CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL		
SIZE		O.D.	O.D.	WIRE RANGE		
	40	1.35 mm	3.05 mm	14 - 20 AWG		
	16	(.053 in)	(.120 in)	(2.0-0.5mm ²)		



PART NUMBER CHART		
COLOR	PART NUMBER	
GREY	AT06-2S-RD01	
BLACK	AT06-2S-RD01BLK	
BLUE	AT06-2S-RD01BLU	
BROWN	AT06-2S-RD01BRN	
GREEN	AT06-2S-RD01GRN	
RED	AT06-2S-RD01RED	
WHITE	AT06-2S-RD01WHT	
YELLOW	AT06-2S-RD01YEL	
ORANGE	AT06-2S-RD01ORG	

STANDARD MOLDED COLOR IS GREY.
ADDITIONAL COLORS SHOWN IN PART NUMBER
CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	UMBER C	HART		REF: DT06-2S-C015, DT06-2S-CE06			
	PART N	NUMBER			DESCRIPTION			ITEM
QUANTITY		7	MAT	ERI	ALS LI	ST		
UNLESS OTHER		SIGN	ATURES	DATE		mnha	\nol	
All dimensions are in metric(mm). Tolerances are as follows:		DRAWN:	LOUIE	23NOV20		mphe		
1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08	Fractions ±1/64 Angles ±1°	CHECKED:	ORION	25NOV20	20 Sine Systems - www.amphenol-sine.com			
3) Note reference = X		ENGINEER:			1	44724 Morley Drive		
		APPROVAL:	TOMMY	27NOV20		Clinton Township, MI 48	036	
		CUSTOMER:			PLI	JG, 2 SOCKET, AT	SERIES,	
			S IS SUPPLIED F		REDI	JCED DIAMETER V	WIRE SEAL	
PROCESS SPECIFICATIONS:		SPECIFICATION SHOWN HERE THE AMPHENC OF REPRODUC	ONLY. DESIGN NS AND PERFO ON ARE THE PR OL CORPORATIO CTION ARE IMPL ARE SUBJECT TO	RMANCE DATA ROPERTY OF DN. NO RIGHTS LIED. ALL	B C-	AT06-2S-RD		A5
		MANUFACTUR		S.	SCALE: NONE		SHEET 1 OF	1

A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins			
Part Number	Description	Size	AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined

Tooling - Machined Contacts				
Part Number	Part Number Description			
AUTK-20	Hand Crimp Tool, Size 20			
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20			
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20			
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20			

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)		
Part Number	Description	
ATRT-100	Contact and Wedgelock Extraction Tool	
AT11-310-1605	Contact Removal Tool, Plastic, Size 16	

	Sealing Plugs (For both Machined or Stamped & Formed Contacts)		
Part Number	Description		
A114017	Sealing Plug, Size 16, White		
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black		
AT13-217-1605	Locking Sealing Plug, Size 16, Grey		
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red		

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

Tooling - Stamped & Formed Contacts			
MFX-3950	Crimp Die - Size 16, 18-20AWG		
MFX-3953	Crimp Die - Size 16, 16-18AWG		
MFX-3975	Crimp Die - Size 16, 14-16AWG		
MFX-3990	Crimp Die - Size 16, 20-22AWG		
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG		
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG		
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG		